

INDUSTRIAL COMPONENT DATA

T5B-7-15866/E 214788 Y7-214788 EATON ELECTRIC

Reversing multi-speed switch, contacts: 12, 63 A, 2 speeds, 2

..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-7-15866/E



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-7-15866/E
Catalog number	Y7-214788
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-8F7BC500CD
Generated	2026-08-04

Product Overview

Reversing multi-speed switch, contacts: 12, 63 A, 2 speeds, 2 rotation directions, Dahlander, front plate: 2-1-0-1-2, 45°, maintained, flush mounting

T5B-7-15866/E

Eaton Moeller® series T5B Reversing multi-speed switches, T5B, 63 A, flush mounting, 7 contact unit(s), Contacts: 12, 45 °, maintained, With 0 (Off) position, 2-1-0-1-2, Design number 15866

Reversing multi-speed switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 12, Degree of Protection: Front IP65, Design: flush mounting, switching function: 2 speeds, 2 operating directions, One tapped winding, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-1-0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Reversing multi-speed switch Catalog Number 214788 Model Code

T5B-7-15866/E EAN 4015082147884 Product Length/Depth 190 mm Product Height 88 mm Product Width 88 mm Product Weight 1.13 kg Certifications CSA-C22.2 No. 94

UL File No.: E36332

CSA Class No.: 3211-05

UL 60947-4-1

VDE 0660

IEC/EN 60204

CSA File No.: 012528

UL

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

IEC/EN 60947-3

CSA

CE

IEC/EN 60947 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 214788 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

63 A

Rated operation current I_e at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

37 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-7-15866/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.