

INDUSTRIAL COMPONENT DATA

T5B-7-66/E 091539 Y7-91539 EATON ELECTRIC Reversing multi-speed switches, Contacts: 12, 63 A, One tapped win..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-7-66/E



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-7-66/E
Catalog number	Y7-91539
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-A9F1894C82
Generated	2026-08-04

Product Overview

Reversing multi-speed switches, Contacts: 12, 63 A, One tapped winding, 2 speeds, front plate: 2-1-0-1-2, 45 °, maintained, flush mounting, SOND 28

Multi-speed switch with inversion; 12 poles; 63 A; 2-speed;

Eaton Moeller® series T5B Reversing multi-speed switches, T5B, 63 A, flush mounting, 7 contact unit(s), Contacts: 12, 45 °, maintained, With 0 (Off) position, 2-1-0-1-2, SOND 28, Design number 66

Reversing multi-speed switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Notes: SOND 28, Contacts: 12, Degree of Protection: Front IP65, Design: flush mounting, switching function: One tapped winding, 2 speeds, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-1-0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Reversing multi-speed switch Catalog Number 091539 Model Code T5B-7-66/E EAN 4015080915393 Product Length/Depth 190 mm Product Height 88 mm Product Width 88 mm Product Weight 1.13 kg

Certifications CSA File No.: 012528

CSA-C22.2 No. 94

CSA

UL Category Control No.: NLRV

CSA Class No.: 3211-07

CSA-C22.2 No. 60947-4-1-14

UL File No.: E36332

IEC/EN 60947-3

IEC/EN 60204

UL

IEC/EN 60947

VDE 0660

CE

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 091539 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

63 A

Rated operation current Ie at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

37 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF00731...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-7-66/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.