

INDUSTRIAL COMPONENT DATA

T0-4-SOND*/EA/SVB 907779 Y7-907779 EATON ELECTRIC

Non-standard switch, T0, 20 A, flush mounting, 4 contact u..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-SOND*/EA/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-SOND*/EA/SVB
Catalog number	Y7-907779
Category	Switch disconnecter
Minimum order	10 Pcs
Document ID	EO-8FDF80D850
Generated	2026-08-02

Product Overview

Non-standard switch, T0, 20 A, flush mounting, 4 contact unit(s)

T0-4-SOND*/EA/SVB

Eaton Moeller® series T0 Non-standard switch, T0, 20 A, flush mounting, 4 contact unit(s), Emergency switching off function, With red rotary handle and yellow locking ring

Non-standard switch, Product range: Non-standard switch, Part group reference: T0, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, Notes: customized version according to form, Degree of Protection: Front IP65, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Non-standard switch Catalog Number 907779 Model Code T0-4-SOND*/EA/SVB
Product Length/Depth 130 mm Product Height 74 mm Product Width 65 mm Product Weight 0.166 kg Certifications IEC/EN 60947

IEC/EN 60947-3

VDE 0660

IEC/EN 60204

ETIM for 907779 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Rated operating voltage (EF001435)

690 V

Rated permanent current I_u (EF001389)

20 A

Rated permanent current at AC-23, 400 V (EF011777)

13.3 A

Rated permanent current at AC-21, 400 V (EF009165)

20 A

Rated operation power at AC-3, 400 V (EF001364)

5.5 kW

Rated short-time withstand current I_{cw} (EF007050)

0.32 kA

Rated operation power at AC-23, 400 V (EF007027)

5.5 kW

Switching power at 400 V (EF009166)

5.5 kW

Conditioned rated short-circuit current I_q (EF001444)

6 kA

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No

Motor drive integrated (EF006697)

No

Voltage release optional (EF007491)

No

Device construction (EF008240)

Built-in device fixed built-in techniq...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-SOND*/EA/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.