

INDUSTRIAL COMPONENT DATA

T3-4-SOND*/I2/SVB 207502 Y7-207502 EATON ELECTRIC

Non-standard switch, T3, 32 A, surface mounting, 4 contact..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-SOND*/I2/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T3-4-SOND*/I2/SVB
Catalog number	Y7-207502
Category	Switch disconnecter
Minimum order	10 Pcs
Document ID	EO-82ADC8EDCD
Generated	2026-08-05

Product Overview

Non-standard switch, T3, 32 A, surface mounting, 4 contact unit(s)

T3-4-SOND*/I2/SVB

Non-standard switch, T3, 32 A, surface mounting, 4 contact unit(s), Emergency switching off function, With red rotary handle and yellow locking ring

Non-standard switch, Product range: Non-standard switch, Part group reference: T3, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, Notes: customized version according to form, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Non-standard switch, T3, 32 A, surface mounting, 4 contact unit(s), Emergency switching off function, With red rotary handle and yellow locking ringNon-standard switch, Product range: Non-standard switch, Part group reference: T3, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, Notes: customized version according to form, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program
Product rangeNon-standard switchPart group referenceT3Stop FunctionEmergency switching off functionWith red rotary

handle and yellow locking ringNotescustomized version according to formDegree of ProtectionIP65Designsurface
mountingMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]15 kWRated uninterrupted current [Iu]32 ANote on rated
uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact units4 contact
unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureEnclosed-25 - +40 °COvervoltage category/pollution

degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock resistance12 gMounting positionAs req...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-SOND*/I2/SVB with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.