

INDUSTRIAL COMPONENT DATA

T5B-5-SOND*/EA/SVB 907938 Y7-907938 EATON ELECTRIC

Non-standard switch, T5B, 63 A, flush mounting, 5 contact..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-5-SOND*/EA/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-5-SOND*/EA/SVB
Catalog number	Y7-907938
Category	Switch disconnecter
Minimum order	10 Pcs
Document ID	EO-7A30D7EB50
Generated	2026-08-04

Product Overview

Non-standard switch, T5B, 63 A, flush mounting, 5 contact unit(s)

T5B-5-SOND*/EA/SVB

Non-standard switch, T5B, 63 A, flush mounting, 5 contact unit(s), Emergency switching off function, With red rotary handle and yellow locking ring

Non-standard switch, Product range: Non-standard switch, Part group reference: T5B, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, Notes: customized version according to form, Degree of Protection: Front IP65, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Non-standard switch, T5B, 63 A, flush mounting, 5 contact unit(s), Emergency switching off function, With red rotary handle and yellow locking ring

Non-standard switch, Product range: Non-standard switch, Part group reference: T5B, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, Notes: customized version according to form, Degree of Protection: Front IP65, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204,

Switch-disconnector according to IEC/EN 60947-3

Delivery program

Product rangeNon-standard switchPart group referenceT5BStop FunctionEmergency switching off functionWith red rotary

handle and yellow locking ringNotescustomized version according to formDegree of ProtectionFront IP65Designflush
mountingMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]30 kWRated uninterrupted current [Iu]63 ANote on rated
uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact units5 contact
unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40

°COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-5-SOND*/EA/SVB with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.