

INDUSTRIAL COMPONENT DATA

T3-6-15898/Z 004353 Y7-4353 EATON ELECTRIC Reversing star-delta switches, Contacts: 11, 32 A, front plate: D..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-6-15898/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-6-15898/Z
Catalog number	Y7-4353
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-BE9BBABB2A
Generated	2026-08-05

Product Overview

Reversing star-delta switches, Contacts: 11, 32 A, front plate: D-Y-0-Y-D, 60 °, maintained, rear mounting, SOND 29 Switch Star-delta with reversing; 11-pole; 32; rating Plate: D-y-0-y-D; 60 °; Interlocking; Installation bottom panel; SOND 29 Eaton Moeller® series T3 Reversing star-delta switches, T3, 32 A, rear mounting, 6 contact unit(s), Contacts: 11, 60 °, maintained, With 0 (Off) position, D-Y-0-Y-D, SOND 29, Design number 15898

Turnaround star-delta switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 29, Contacts: 11, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: D-Y-0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Turnaround star-delta switch Catalog Number 004353 Model Code T3-6-15898/Z
EAN 4015080043539 Product Length/Depth 179 mm Product Height 54 mm Product Width 61 mm Product Weight 0.366 kg

Certifications IEC/EN 60204

UL File No.: E36332

CE

IEC/EN 60947-3

UL Category Control No.: NLRV

IEC/EN 60947

CSA File No.: 012528

CSA Class No.: 3211-05

CSA-C22.2 No. 94

CSA

CSA-C22.2 No. 60947-4-1-14

UL

UL 60947-4-1

VDE 0660 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 004353 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Turnaround star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

18.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-6-15898/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.