

INDUSTRIAL COMPONENT DATA

MSC-R-0,25-M7(24VDC) 283190 Y7-283190 EATON ELECTRIC Reversing starter, 3p, 0.06kW/400V/AC3, 150kA

Brand: EATON - MOELLER | Manufacturer Part Number: MSC-R-0,25-M7(24VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	MSC-R-0,25-M7(24VDC)
Catalog number	Y7-283190
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-90C53B569B
Generated	2026-08-06

Product Overview

Reversing starter, 3p, 0.06kW/400V/AC3, 150kA

MSC-R-0,25-M7(24VDC)

Eaton Moeller® series MSC-R Reversing starter, 380 V 400 V 415 V: 0.06 kW, Ir= 0.16 - 0.25 A, 24 V DC, DC voltage MSC-R-0,25-M7(24VDC)

Reversing starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor rating at AC-3, 380 V 400 V 415 V: P= 0.06 kW, Setting range of overload releases: Ir= 0.16 - 0.25 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 24 V DC, DC voltage, Standards: UL 508 (on request), CSA C 22.2 No. 14 (on request)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series MSC-R Reversing starter Catalog Number 283190 Model Code

MSC-R-0,25-M7(24VDC) EAN 4015082831905 Product Length/Depth 185 mm Product Height 95 mm Product Width 90 mm Product Weight 1 kg Certifications CSA File No.: 012528

IEC/EN 60947-4-1

UL File No.: E123500

CSA

CSA Class No.: 3211-24

UL
UL 508 (on request)
CE
UL60947-4-1A
CSA-C22.2 No. 14-10
UL Category Control No.: NKJH
CSA-C22.2 No. 14 (on request) Features & Functions
Fitted with: Short-circuit release Functions Temperature compensated overload protection General
Class CLASS 10 A Connection Screw terminals Connection to SmartWire-DT No Coordination type 2 Degree of protection
IP20
NEMA Other Model IEC/UL starter Mounting method DIN rail Number of auxiliary contacts (normally closed contacts) 0
Number of auxiliary contacts (normally open contacts) 0 Overload release current setting - min 0.16 A Overload release
current setting - max 0.25 A Overvoltage category III Pollution degree 3 Rated impulse withstand voltage (Uimp) 6000 V AC
Suitable for Also motors with efficiency class IE3 Type Starter with Bi-Metal release Voltage type DC Climatic environmental
conditions
Altitude Max. 2000 m Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Electrical
rating
Rated operational current (Ie) 0.21 A Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V 0.25 A Rated operational
power at AC-3, 220/230 V, 50 Hz 0.04 kW Rated operational p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MSC-R-0,25-M7(24VDC) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.