

INDUSTRIAL COMPONENT DATA

MSC-R-25-M25(230V50HZ)/BBA 102995 XTSR025B025CFNL-A EATON ELECTRIC Reversing starter, 3p, 11kW/400V/AC3, 50k..

Brand: EATON - MOELLER | Manufacturer Part Number: MSC-R-25-M25(230V50HZ)/BBA



Manufacturer	EATON - MOELLER
MPN / Reference	MSC-R-25-M25(230V50HZ)/BBA
Catalog number	XTSR025B025CFNL-A
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-1F525F7566
Generated	2026-08-05

Product Overview

Reversing starter, 3p, 11kW/400V/AC3, 50kA, +busbar adapter

Inverter Motor Starter; 11 kW; 400V; AC-3; 50 kA ; 230 V 50 Hz; With busbar adapter

Reversing starter, 380 V 400 V 415 V: 11 kW, Ir= 20 - 25 A, 230 V 50 Hz, 240 V 60 Hz, AC voltage

Reversing starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor ratings Motor rating AC-3 380 V 400 V 415 V: P= 11 kW, Setting range of overload releases: Ir= 20 - 25 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, AC voltage, Standards: UL 508 (on request), CSA C 22.2 No. 14 (on request)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

Reversing starter, 380 V 400 V 415 V: 11 kW, Ir= 20 - 25 A, 230 V 50 Hz, 240 V 60 Hz, AC voltage Reversing starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor ratings Motor rating AC-3 380 V 400 V 415 V: P= 11 kW, Setting range of overload releases: Ir= 20 - 25 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, AC voltage, Standards: UL 508 (on request), CSA C 22.2 No. 14 (on request) Delivery program

Basic function Reversing starters (completed devices) Basic device MSC Notes Also suitable for motors with efficiency class IE3.

IE3-ready devices are identified by the logo on their packaging. Connection to SmartWire-DT no Motor ratings Motor rating [P]AC-3380 V 400 V 415 V [P] 11 kW Rated operational currentAC-3380 V 400 V 415 V [Ie] 21.7 A Rated short-circuit current 380 - 415 V [Iq] 50 kA Setting range Setting range of overload releases[Ir] 20 - 25 A Coordination Type of coordination "1"

Type of coordination "2" Contact sequence Actuating voltage 230 V 50 Hz, 240 V 60 Hz AC voltage Motor-protective circuit-breakers PKZM0-25 Type Contactor DILM25-01(...) Part no. DOL starter wiring set

Mechanical connection element and electrical electric contact module PKZM0-XM32DE + DILM32-XRL Type Notes The reversing starter (complete units) consists of a PKZM0 motor protective circuit breaker and two DILM contactors. These....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MSC-R-25-M25(230V50HZ)/BBA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.