

INDUSTRIAL COMPONENT DATA

**MSC-R-10-M17(24VDC) 101051 XTSR010B018CTDNL EATON
ELECTRIC Reversing starter, 3p, 4.0kW/400V/AC3, 100kA**

Brand: EATON - MOELLER | Manufacturer Part Number: MSC-R-10-M17(24VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	MSC-R-10-M17(24VDC)
Catalog number	XTSR010B018CTDNL
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-C0B5FB7CC5
Generated	2026-08-06

Product Overview

Reversing starter, 3p, 4.0kW/400V/AC3, 100kA

Inverter Motor Starter; 4.0 kW; 400V; AC-3; 100 kA; 24 V DC

Reversing starter, 380 V 400 V 415 V: 3 kW, Ir= 6.3 - 10 A, 24 V DC, DC voltage

Reversing starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor ratings Motor rating AC-3 380 V 400 V 415 V: P= 3 kW, Setting range of overload releases: Ir= 6.3 - 10 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 24 V DC, DC voltage, Standards: UL 508 (on request), CSA C 22.2 No. 14 (on request)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

Reversing starter, 380 V 400 V 415 V: 3 kW, Ir= 6.3 - 10 A, 24 V DC, DC voltage Reversing starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor ratings Motor rating AC-3 380 V 400 V 415 V: P= 3 kW, Setting range of overload releases: Ir= 6.3 - 10 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 24 V DC, DC voltage, Standards: UL 508 (on request), CSA C 22.2 No. 14 (on request) Delivery program

Basic function Reversing starters (completed devices) Basic device MSC Notes Also suitable for motors with efficiency class IE3.

IE3-ready devices are identified by the logo on their packaging. Connection to SmartWire-DT no Motor ratings Motor rating [P]AC-3380 V 400 V 415 V [P] 3 kW Rated operational currentAC-3380 V 400 V 415 V [Ie] 6.6 A Rated short-circuit current

380 - 415 V [Iq] 50 kA Setting range Setting range of overload releases[Ir] 6.3 - 10 A Coordination Type of coordination "1"
Type of coordination "2" Contact sequence Actuating voltage 24 V DC DC voltage Motor-protective circuit-breakers
PKZM0-10 Type Contactor DILM17-01(...) Part no. DOL starter wiring set
Mechanical connection element and electrical electric contact module PKZM0-XRM32 Type Notes The reversing starter
(complete unit) consists of a PKZM0 motor-protective circuit-breaker and two DILM contactors.
With the adapter-less top-hat rail mounting of starters up to 12 A, onl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MSC-R-10-M17(24VDC) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.