

INDUSTRIAL COMPONENT DATA

T0-3-123/I1 222632 Y7-222632 EATON ELECTRIC Reversing switches, Contacts: 6, 20 A, front plate: 2-0-1, 90 °,..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-123/I1



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-123/I1
Catalog number	Y7-222632
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-9172041121
Generated	2026-08-06

Product Overview

Reversing switches, Contacts: 6, 20 A, front plate: 2-0-1, 90 °, maintained, surface mounting, SOND 30
T0-3-123/I1

Eaton Moeller® series T0 Reversing switches, T0, 20 A, surface mounting, 3 contact unit(s), Contacts: 6, 60 °, maintained, With 0 (Off) position, 2-0-1, SOND 30, Design number 123

Reversing switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 30, Contacts: 6, Degree of Protection: IP65, Design: surface mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Reversing switch Catalog Number 222632 Model Code T0-3-123/I1 EAN 4015082226329 Product Length/Depth 137 mm Product Height 122 mm Product Width 80 mm Product Weight 0.288 kg

Certifications IEC/EN 60204

IEC/EN 60947-3

VDE 0660

IEC/EN 60947 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 222632 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

20 A

Rated operation current I_e at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

Yes

Housing material (EF001596)

Plastic

Type of control element (EF006976)

Short thumb-grip

Type of electrical connection of main circuit (EF006819)

Screw connection

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-123/I1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.