

INDUSTRIAL COMPONENT DATA

T5B-3-8401/I4 207227 Y7-207227 EATON ELECTRIC Reversing switches, Contacts: 5, 63 A, front plate: 1-0-2, 60 ..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-3-8401/I4



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-3-8401/I4
Catalog number	Y7-207227
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-B27A4A7E3F
Generated	2026-08-06

Product Overview

Reversing switches, Contacts: 5, 63 A, front plate: 1-0-2, 60 °, maintained, surface mounting

T5B-3-8401/I4

Eaton Moeller® series T5B Reversing switches, T5B, 63 A, surface mounting, 3 contact unit(s), Contacts: 5, 60 °, maintained, With 0 (Off) position, 1-0-2, Design number 8401

Reversing switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 5, Degree of Protection: IP65, Design: surface mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Reversing switch Catalog Number 207227 Model Code T5B-3-8401/I4 EAN 4015082072278 Product Length/Depth 240 mm Product Height 197 mm Product Width 160 mm Product Weight 1.303 kg

Certifications VDE 0660

CSA Class No.: 3211-05

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

UL

CSA

CE

CSA-C22.2 No. 94

IEC/EN 60204

IEC/EN 60947-3

UL File No.: E36332

UL 60947-4-1

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 207227 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

63 A

Rated operation current Ie at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

22 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

Yes

Housing m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-3-8401/I4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.