

INDUSTRIAL COMPONENT DATA

T0-3-2/E 001619 Y7-1619 EATON ELECTRIC Reversing switches, Contacts: 5, 20 A, front plate: 2-0-1, 45 °, main..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-2/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-2/E
Catalog number	Y7-1619
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-F31857F6CC
Generated	2026-08-05

Product Overview

Reversing switches, Contacts: 5, 20 A, front plate: 2-0-1, 45 °, maintained, flush mounting
Reversing switch; 5-pole; 20a; rating Plate: 2-0-1; 45 °; Interlock; recessed Mounting
Eaton Moeller® series T0 Reversing switches, T0, 20 A, flush mounting, 3 contact unit(s), Contacts: 5, 45 °, maintained, With 0 (Off) position, 2-0-1, Design number 2
Reversing switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 5, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Reversing switch Catalog Number 001619 Model Code T0-3-2/E EAN 4015080016199 Product Length/Depth 95 mm Product Height 48 mm Product Width 48 mm Product Weight 0.127 kg
Certifications CSA-C22.2 No. 94
IEC/EN 60947-3
UL File No.: E36332
VDE 0660

CSA

CSA Class No.: 3211-05

CSA File No.: 012528

IEC/EN 60947

UL Category Control No.: NLRV

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

UL

CE

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 001619 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

20 A

Rated operation current I_e at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-2/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.