

INDUSTRIAL COMPONENT DATA

T0-2-8400/Z 062571 Y7-62571 EATON ELECTRIC Reversing switches, Contacts: 4, 20 A, front plate: 1-0-2, 45 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-8400/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-8400/Z
Catalog number	Y7-62571
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-B6F15C9BD8
Generated	2026-08-03

Product Overview

Reversing switches, Contacts: 4, 20 A, front plate: 1-0-2, 45 °, maintained, rear mounting

Inverter switch; 4 poles; 20 A; Indicator plate: 1-0-2; 45 °;

Eaton Moeller® series T0 Reversing switches, T0, 20 A, rear mounting, 2 contact unit(s), Contacts: 4, 45 °, maintained, With 0 (Off) position, 1-0-2, Design number 8400

Reversing switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 4, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Reversing switch Catalog Number 062571 Model Code T0-2-8400/Z EAN 4015080625711 Product Length/Depth 128 mm Product Height 48 mm Product Width 48 mm Product Weight 0.134 kg

Certifications IEC/EN 60947

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-3

UL
CE
UL File No.: E36332
CSA
UL Category Control No.: NLRV
VDE 0660
CSA-C22.2 No. 94
CSA Class No.: 3211-05
CSA File No.: 012528
IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 062571 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Reversing switch
Number of poles (EF001391)
2
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current I_u (EF001389)
20 A
Rated operation current I_e at AC-3, 400 V (EF001392)
11.5 A
Rated operation power at AC-3, 400 V (EF001364)
4 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
Yes
Complete device in housing (EF007317)
No

Housing mater...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-8400/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.