

## INDUSTRIAL COMPONENT DATA

# T0-3-8401/XZ 005739 Y7-5739 EATON ELECTRIC Reversing switches, Contacts: 5, 20 A, 60 °, rear mounting, Basic..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-8401/XZ



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-3-8401/XZ    |
| Catalog number  | Y7-5739         |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-8B83448429   |
| Generated       | 2026-08-06      |

## Product Overview

Reversing switches, Contacts: 5, 20 A, 60 °, rear mounting, Basic switch

5-pole inverter switch 20 A Indicator plate: 1-0-2 60°

Reversing switches, T0, 20 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 5, 60 °, design no. 8401

Reversing switch, Product range: Control switches, Part group reference: T0, Contacts: 5, Design: rear mounting, Basic switch, Switching angle: 60 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I<sub>u</sub> = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                  |
|--------------|--------------------------------------------------|
| Catalog path | EATON - MOELLER > Disconnectors and Cam Switches |
|--------------|--------------------------------------------------|

## Additional Product Information

EL-Nummer (Norway)1456677Reversing switches, T0, 20 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 5, 60 °, design no. 8401Reversing switch, Product range: Control switches, Part group reference: T0, Contacts: 5, Design: rear mounting, Basic switch, Switching angle: 60 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I<sub>u</sub> = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeControl switchesPart group referenceT0Basic functionReversing switchesContacts5Designrear mounting  
Basic switchContact sequenceSwitching angle60 °Design number8401Front plate no.Motor rating AC-23A, 50 - 60 Hz  
[P]400 V [P]5.5 kWRated uninterrupted current [I<sub>u</sub>]20 ANote on rated uninterrupted current I<sub>u</sub>Rated uninterrupted current  
I<sub>u</sub> is specified for max. cross-section.Number of contact units3 contact unit(s)Technical data  
GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40  
°COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock  
resistance15 gMounting positionAs requiredContactsElectrical characteristicsRated operational voltage [Ue]690 V  
ACElectrical characteristicsRated uninterrupted current [Iu]20 AElect...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-8401/XZ with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.