

INDUSTRIAL COMPONENT DATA

T0-3-8426/E 000982 Y7-982 EATON ELECTRIC Cam switch, Ie: 20A to 440V AC-21

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-8426/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-8426/E
Catalog number	Y7-982
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-21D5DB5A90
Generated	2026-08-02

Product Overview

Cam switch, Ie: 20A to 440V AC-21

Auxiliary winding switch 6 poles 20 A Indicator plate:

Eaton Moeller® series T0 Auxiliary winding switch, T0, 20 A, flush mounting, 3 contact unit(s), Contacts: 6, 45 °, maintained, With 0 (Off) position, with spring-return from both directions to 0, 2-START>0

Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, with spring-return from both directions to 0, 3 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 2-START>0

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Auxiliary winding switch Catalog Number 000982 Model Code T0-3-8426/E EAN 4015080009825 Product Length/Depth 95 mm Product Height 48 mm Product Width 48 mm Product Weight 0.121 kg

Certifications CSA-C22.2 No. 94

CSA File No.: 012528

UL Category Control No.: NLRV

VDE 0660

CE
UL File No.: E36332
CSA Class No.: 3211-05
UL 60947-4-1
IEC/EN 60947
IEC/EN 60947-3
IEC/EN 60204
CSA
CSA-C22.2 No. 60947-4-1-14
UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 000982 Low-voltage industrial controls and switchgear (EC002611)
Feature Name
Feature Value
Type of switch (EF003496)
Reverser
Number of poles (EF001391)
2
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated permanent current Iu (EF001389)
20 A
Number of switch positions (EF000231)
5
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
Yes
Device construction (EF008240)
Built-in device
Width in number of modular spacings (EF002950)
0
Suitable for floor mounting (EF007243)
No
Suitable for front mounting (EF007246)
Yes
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)
No
Type of control element (EF006976)
Toggle
Front shield size (EF007176)
48x48 mm
Degree of protection (IP), front side (EF003118)
IP65

Degree of protection (NEMA), front side (EF011961)
12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-8426/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.