

INDUSTRIAL COMPONENT DATA

T3-2-8515/EZ 018528 Y7-18528 EATON ELECTRIC Universal control switches, Contacts: 4, 32 A, front plate: AUSL..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-8515/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-8515/EZ
Catalog number	Y7-18528
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-95B25192CA
Generated	2026-08-03

Product Overview

Universal control switches, Contacts: 4, 32 A, front plate: AUSL>Aus

Universal Control Switch 4-Pole 32 A Indicator Plate:

Eaton Moeller® series T3 Universal control switches, T3, 32 A, center mounting, 2 contact unit(s), Contacts: 4, 45 °, momentary, With spring-return from both directions to OFF, AUSL>Aus

Universal control switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 4, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 45 °, Switching performance: momentary, With spring-return from both directions to OFF, 2 contact unit(s), Rated uninterrupted current: I_u= 32 A, front plate: AUSL>Aus

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Universal control switch Catalog Number 018528 Model Code T3-2-8515/EZ EAN 4015080185284 Product Length/Depth 113 mm Product Height 54 mm Product Width 61 mm Product Weight 0.179 kg

Certifications IEC/EN 60947

CSA

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

CSA File No.: 012528

VDE 0660

UL File No.: E36332

CSA-C22.2 No. 94

IEC/EN 60204

UL

CSA Class No.: 3211-05

IEC/EN 60947-3

UL Category Control No.: NLRV

CE Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 018528 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Group switch

Number of poles (EF001391)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

32 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-8515/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.