

## INDUSTRIAL COMPONENT DATA

# T3-2-SOND\*/EA/SVB-SW 908081 Y7-908081 EATON ELECTRIC

## Non-standard switch, T3, 32 A, flush mounting, 2 contac..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-SOND\*/EA/SVB-SW



|                 |                      |
|-----------------|----------------------|
| Manufacturer    | EATON - MOELLER      |
| MPN / Reference | T3-2-SOND*/EA/SVB-SW |
| Catalog number  | Y7-908081            |
| Category        | Switch disconnecter  |
| Minimum order   | 10 Pcs               |
| Document ID     | EO-6E2965B155        |
| Generated       | 2026-08-04           |

## Product Overview

Non-standard switch, T3, 32 A, flush mounting, 2 contact unit(s)

T3-2-SOND\*/EA/SVB-SW

Non-standard switch, T3, 32 A, flush mounting, 2 contact unit(s), STOP function, With black rotary handle and locking ring

Non-standard switch, Product range: Non-standard switch, Part group reference: T3, Stop Function: STOP function, With

black rotary handle and locking ring, Notes: customized version according to form, Degree of Protection: Front IP65,

Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I<sub>u</sub> = 32 A, 2

contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

Non-standard switch, T3, 32 A, flush mounting, 2 contact unit(s), STOP function, With black rotary handle and locking

ringNon-standard switch, Product range: Non-standard switch, Part group reference: T3, Stop Function: STOP function,

With black rotary handle and locking ring, Notes: customized version according to form, Degree of Protection: Front IP65,

Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I<sub>u</sub> = 32 A, 2

contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN

60947-3Delivery program

Product rangeNon-standard switchPart group referenceT3Stop FunctionSTOP functionWith black rotary handle and locking

ringNotescustomized version according to formDegree of ProtectionFront IP65Designflush mountingMotor rating AC-23A,

50 - 60 Hz [P]400 V [P]15 kWRated uninterrupted current [I<sub>u</sub>]32 ANote on rated uninterrupted current I<sub>u</sub>Rated uninterrupted

current I<sub>UIS</sub> specified for max. cross-section. Number of contact units 2 contact unit(s) Technical data  
General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204  
Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open -25 - +50 °C Ambient temperature Enclosed -25 - +40  
°C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [U<sub>imp</sub>] 6000 V AC Mechanical shock  
resistance 15 g Mounting position As required Contacts Electrical charact...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-SOND\*/EA/SVB-SW with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.