

INDUSTRIAL COMPONENT DATA

T3-3-8401/Z 035739 Y7-35739 EATON ELECTRIC Reversing switches, Contacts: 5, 32 A, front plate: 1-0-2, 60 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-3-8401/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-3-8401/Z
Catalog number	Y7-35739
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-E3CD8E3B40
Generated	2026-08-05

Product Overview

Reversing switches, Contacts: 5, 32 A, front plate: 1-0-2, 60 °, maintained, rear mounting

Switch Inverter 5 poles 32 A Indicator plate: 1-0-2 45°

Eaton Moeller® series T3 Reversing switches, T3, 32 A, rear mounting, 3 contact unit(s), Contacts: 5, 60 °, maintained, With 0 (Off) position, 1-0-2, Design number 8401

Reversing switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 5, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Reversing switch Catalog Number 035739 Model Code T3-3-8401/Z EAN 4015080357391 Product Length/Depth 144 mm Product Height 54 mm Product Width 61 mm Product Weight 0.237 kg

Certifications CE

IEC/EN 60947

UL File No.: E36332

VDE 0660

CSA File No.: 012528

UL

IEC/EN 60204

IEC/EN 60947-3

UL Category Control No.: NLRV

CSA

CSA-C22.2 No. 60947-4-1-14

CSA-C22.2 No. 94

CSA Class No.: 3211-05

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 035739 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Housing mate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-3-8401/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.