

INDUSTRIAL COMPONENT DATA

T5B-3-50/E 092402 Y7-92402 EATON ELECTRIC Multi-speed switches, Contacts: 6, 63 A, 2 speeds, front plate: 1-..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-3-50/E



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-3-50/E
Catalog number	Y7-92402
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-0A466D1878
Generated	2026-08-02

Product Overview

Multi-speed switches, Contacts: 6, 63 A, 2 speeds, front plate: 1-2, 90 °, maintained, flush mounting

Multi-speed switch 6 poles 63 A 2 speed Plate

Eaton Moeller® series T5B Multi-speed switches, T5B, 63 A, flush mounting, 3 contact unit(s), Contacts: 6, 90 °, maintained, Without 0 (Off) position, 1-2, Design number 50

Multi-speed switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 6, Degree of Protection: Front IP65, Design: flush mounting, switching function: 2 speeds, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, front plate: 1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Multi-speed switch Catalog Number 092402 Model Code T5B-3-50/E EAN 4015080924029 Product Length/Depth 124 mm Product Height 88 mm Product Width 88 mm Product Weight 0.59 kg

Certifications IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

VDE 0660

IEC/EN 60947-3

UL 60947-4-1

CSA-C22.2 No. 94

IEC/EN 60204

CSA Class No.: 3211-07

CE

UL File No.: E36332

CSA File No.: 012528

CSA

UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 092402 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Pole switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

63 A

Rated operation current Ie at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

22 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-3-50/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.