

INDUSTRIAL COMPONENT DATA

RMQ-M1C-ASI 032314 EATON ELECTRIC Connection, as well, of RMQ22, for surface mounting enclosure

Brand: EATON - MOELLER | Manufacturer Part Number: RMQ-M1C-ASI



Manufacturer	EATON - MOELLER
MPN / Reference	RMQ-M1C-ASI
Catalog number	Y7-32314
Category	Accessories/spare parts for command devices
Minimum order	1 Pcs
Document ID	EO-B9786D1273
Generated	2026-08-06

Product Overview

Connection, as well, of RMQ22, for surface mounting enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Connection, asi, of RMQ22, for surface mounting enclosureAccessories for the control circuit devices programDelivery program

Product rangeAccessoriesAccessoriesAS-InterfaceBasic function accessoriesAS-Interface connectionFixingFront fixing for RMQ-TitanExternal connections: 4 inputs/4 outputs

For contact and lamp socket elements.

RMQ-Titan surface mounting enclosures: M22-I3, M22-I4, M22-I6Connection to SmartWire-DTnoTechnical data

GeneralStandardsEN 50081-1

EN 50082-1Radio interference suppressionEN 55011, EN 55022Limit value classADegree of ProtectionIP20Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +55 °CMechanical shock resistance> 30

Shock duration 11 ms gVibration to IEC 60068-2-27 (amplitude 1 mm)1055 HzDimensions92 x 46 x 30 mmWeight0.1 kg

FixingFront fixing for RMQ-TitanMounting positionAs requiredPower supplyRated voltage to AS-Interface Specification26.5 - 31.6 V DCPower supplyCompletely from the AS-Interface cableAddressingVia connection to AS-Interface cableAS-InterfaceProtected against polarity reversalRated operational current at full load120 mARated operational current when idle (no I, O set)30 mAStatus LEDsAS-Interface voltage: green LEDInputsVoltage range24 - 30 V

DCRated current per input3.5 mAHigh signal level? 15 VLength of connecting cables200 cmOutputsOutputs, protected against short-circuit4 NumberVoltage range24 V DC (+10/-15%) V DCMax. current carrying capacity? 3 external out...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RMQ-M1C-ASI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.