

INDUSTRIAL COMPONENT DATA

LS-XLB 290178 Y7-290178 EATON ELECTRIC Roller lever, long

Brand: EATON - MOELLER | Manufacturer Part Number: LS-XLB



Manufacturer	EATON - MOELLER
MPN / Reference	LS-XLB
Catalog number	Y7-290178
Category	Drive head for position switches/hinge switches
Minimum order	5 Pcs
Document ID	EO-F3DBDB3632
Generated	2026-08-03

Product Overview

Roller lever, long

LS-XLB

Eaton Moeller® series LS Roller lever, large

Operating head for LS-Titan position switch, IEC EN 60947-5-1, high degree of protection IP66, device for world markets, modular system, easy mounting technology operating heads can be attached in any 4 directions and snapped on simple, quick and safely using the bayonet fitting.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Position Switches
--------------	-------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series LS Roller lever Catalog Number 290178 Model Code LS-XLB EAN 4015082901783

Product Length/Depth 33.5 mm Product Height 45 mm Product Width 31 mm Product Weight 0.012 kg Compliances CE

Marked Certifications IEC 60947-5

EN 60947-5

UL 508

CSA Std. C22.2 No. 14

CE

CSA

CSA-C22.2 No. 14

UL
IEC/EN 60947-5
CSA File No.: 012528
UL File No.: E29184
CSA Class No.: 3211-03
UL Category Control No.: NKCR Catalog Notes Large Features & Functions
Design EN 50047 Form E Features The operating head can be rotated 90° to enable adaptation to the specified approach direction General
Product category Roller lever Type Operating heads Climatic environmental conditions
Ambient operating temperature - min -40 °C Ambient operating temperature - max 70 °C Actuator
Actuator type Roller lever Design verification
Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LS-XLB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.