

**INDUSTRIAL COMPONENT DATA**

# K2SDR/C 1818039 Y8-1818039 EATON ELECTRIC Rotary handle, 6mm, door installation, red/yellow, cylinder lock

Brand: EATON - MOELLER | Manufacturer Part Number: K2SDR/C



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | EATON - MOELLER                  |
| MPN / Reference | K2SDR/C                          |
| Catalog number  | Y8-1818039                       |
| Category        | Handle for power circuit breaker |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-E844AEA792                    |
| Generated       | 2026-08-04                       |

## Product Overview

Rotary handle, 6mm, door installation, red/yellow, cylinder lock

K2SDR/C

Rotary handle, Basic function: Rotary handles, Complete handle with door coupling, Shaft diameter: 6 x 6, For use with: DMM125, DMV160N, For use with: Door build in installation, Information about equipment supplied: With cylinder lock, red/yellow, Switching angle: 90 °

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                               |
|--------------|-----------------------------------------------|
| Catalog path | EATON - MOELLER > DUMECO Switch-Disconnectors |
|--------------|-----------------------------------------------|

## Additional Product Information

**General specifications**

Product Name Eaton K2 Accessory Handle Catalog Number 1818039 Model Code K2SDR/C EAN 8711426958418 Product Length/Depth 240 mm Product Height 30 mm Product Width 120 mm Product Weight 0.192 kg Compliances CE Features & Functions

Color Red Features Lockable Fitted with: Key lock Locking mechanism Cylinder lock General

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Degree of protection NEMA Other

Shaft diameter 6 x 6 mm Suitable for Power circuit breaker

Switch disconnecter Switching angle 90 ° Type Complete rotary handle with door coupling Design verification

Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdis 0 W Heat dissipation per pole, current-dependent Pvid 0 W Rated operational current for specified heat dissipation (In) 0 A Static heat dissipation, non-current-dependent Pvs 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6 Mechanical im...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / K2SDR/C with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.