

INDUSTRIAL COMPONENT DATA

LS-XRL 266126 Y7-266126 EATON ELECTRIC 266126 LS-XRL

Brand: EATON - MOELLER | Manufacturer Part Number: LS-XRL



Manufacturer	EATON - MOELLER
MPN / Reference	LS-XRL
Catalog number	Y7-266126
Category	Drive head for position switches/hinge switches
Minimum order	5 Pcs
Document ID	EO-2B6A593DD0
Generated	2026-08-02

Product Overview

266126 LS-XRL

LS-XRL

Eaton Moeller® series LS Rotary lever

Operating head for LS-Titan position switch, IEC EN 60947-5-1, high degree of protection IP66, device for world markets, modular system, easy mounting technology operating heads can be attached in any 4 directions and snapped on simple, quick and safely using the bayonet fitting.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series LS Rotary lever Catalog Number 266126 Model Code LS-XRL EAN 4015082661267

Product Length/Depth 25 mm Product Height 49 mm Product Width 46 mm Product Weight 0.016 kg Compliances CE

Marked Certifications EN 60947-5

IEC 60947-5

UL 508

CSA Std. C22.2 No. 14

UL File No.: E29184

CE

UL Category Control No.: NKCR

CSA

CSA Class No.: 3211-03

IEC/EN 60947-5

UL

CSA File No.: 012528

CSA-C22.2 No. 14 Features & Functions

Design EN 50047 Form A Features The operating head can be rotated 90° to enable adaptation to the specified approach direction General

Product category Rotary lever Type Operating heads Climatic environmental conditions

Ambient operating temperature - min -40 °C Ambient operating temperature - max 70 °C Actuator

Actuator type Rotary lever Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's req...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LS-XRL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.