

INDUSTRIAL COMPONENT DATA

RA-C2-S1-4 257830 Y7-257830 EATON ELECTRIC Round conductor outgoer, 1-fold, 2.5-4qmm

Brand: EATON - MOELLER | Manufacturer Part Number: RA-C2-S1-4



Manufacturer	EATON - MOELLER
MPN / Reference	RA-C2-S1-4
Catalog number	Y7-257830
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-A0B6BCDAB0
Generated	2026-08-05

Product Overview

Round conductor outgoer, 1-fold, 2.5-4qmm

RA-C2-S1-4

Round cable power bus branch for powering Rapid Link devices via adapter cable, IDC cable termination

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Rapid Link Starters

Additional Product Information

Round conductor outgoer, 1-fold, 2.5-4qmmRound cable power bus branch for powering Rapid Link devices via adapter cable, IDC cable termination

General specificationsProduct nameEaton Moeller® series Rapid Link Accessory Connection socketPart no.RA-C2-S1-4EAN4015082578305Product Length/Depth158 millimetreProduct height55 millimetreProduct width112.5 millimetreProduct weight0.328 kilogramCertificationsEN 60664-1

DESINA

IEC/EN 60529

EN 61684Product TradenameRapid LinkProduct TypeAccessoryProduct Sub TypeConnection socketFeatures & FunctionsEnclosure materialPolycarbonateFitted with:A pair of gaskets for these cable diameters

Lock mechanismLocking facilityMaterial of locking facility: Polyamide (PA)General informationAccessories1 lock mechanism and 1 pairs of gaskets for these cable diameters included with supplied equipment.Accessory/spare part typeConnection techniqueDegree of protectionIP65, according to IEC/EN 60529Product categoryAccessoriesTypeConnection socket (for power connection cable)Ambient conditions, mechanicalMounting positionAs requiredClimatic environmental

conditions Ambient operating temperature - min-30 °C Ambient operating temperature - max50 °C Ambient storage temperature - min-40 °C Ambient storage temperature - max70 °C Main circuit Rated operational current (Ie) 10 A 25 A (4 mm²) Rated operational voltage (Ue) at AC - max690 V Rated operational voltage (Ue) at DC - max24 V Contacts Contact type Piercing/screw terminals Design verification 10.2.2 Corrosion resistance Me...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RA-C2-S1-4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.