

INDUSTRIAL COMPONENT DATA

RT2RSEO400CGL1HIP EATON ELECTRIC RTECH MR SEO CGL+ 400 MNM 1H IP65

Brand: EATON - MOELLER | Manufacturer Part Number: RT2RSEO400CGL1HIP



Manufacturer	EATON - MOELLER
MPN / Reference	RT2RSEO400CGL1HIP
Catalog number	RT2RSEO400CGL1HIP
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-2161DFA81D
Generated	2026-08-03

Product Overview

RTECH MR SEO CGL+ 400 MNM 1H IP65

EATON'S ROUNDTech MEDIUM RECES. SAFETY EFOCUS CGL+ 400 MNM 1H IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Central Battery System

Additional Product Information

General specifications

Product Name Eaton RoundTech MRSEO recessed emergency luminaire Catalog Number RT2RSEO400CGL1HIP EAN 3660191812461 Product Length/Depth 220 mm Product Height 58 mm Product Width 195 mm Product Weight 0.331 kg

Certifications CE marking

CE Product specifications

Battery voltage 3.2 V Battery number of cells 2 Battery quality Lithium-ions Glow wire test 850 °C Permissible ambient temperature - min 5 °C Permissible ambient temperature - max 45 °C Protection class II Outdoor use compliance False Explosion protected False Diameter 110 mm Degree of protection IP65 Mode Maintained / Non-Maintained (M / NM) Lamp type LED not exchangeable With light source True Lamp holder None Type of indicator Not applicable Monitoring equipment Safety module for monitoring (central feeded system) Power supply system Peripheral (individual battery) Voltage type AC Apparent Power At Mains Operation 1.83 VA Power factor .6 Wiring system Continuous circuit/emergency circuit With remote switch connection True Reserve-polarity protected False Conductor cross section 2.5 Connection type Plug-in connection Max. system power 1.1 W Rated life time L70/B10 at 25 °C 60600 hour Rated life time L80/B10 at 25 °C 60600 hour Rated life time L90/B10 at 25 °C 60600 hour Nominal voltage AC - max 230 V Nominal voltage AC - min 230 V

Nominal operation time - min 1 hour Nominal operation time - max 1 hour Mounting Method Surface mounting/recessed mounting Material housing Plastic Color housing Whit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RT2RSEO400CGL1HIP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.