

INDUSTRIAL COMPONENT DATA

S/COND FUSE WITH IND. 175A 500V FWH-175BI EATON

ELECTRIC Fuse-link, high speed, 175 A, AC 500 V, DC 500 V, 2..

Brand: EATON - MOELLER | Manufacturer Part Number: S/COND FUSE WITH IND. 175A 500V



Manufacturer	EATON - MOELLER
MPN / Reference	S/COND FUSE WITH IND. 175A 500V
Catalog number	FWH175BI
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-BD785052E4
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 175 A, AC 500 V, DC 500 V, 29 x 92 mm, aR, UL, with indicator

S/COND FUSE WITH IND. 175A 500V

S/COND FUSE WITH IND. 175A 500V - Fuse-link, high speed, 175 A, AC 500 V, DC 500 V, 200 kA, 29 x 92 mm, aR, UL, with indicator

Fuse, Fuse-link, high speed, 175 A, AC 500 V, DC 500 V, 29 x 92 mm, aR, UL, with indicator, cylindrical, centre-bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL 248, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 175 A, AC 500 V, DC 500 V, 200 kA, 29 x 92 mm, aR, UL, with indicator
Fuse, Fuse-link, high speed, 175 A, AC 500 V, DC 500 V, 29 x 92 mm, aR, UL, with indicator, cylindrical, centre-bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL 248, Breaking Capacity 200 kA
Delivery program
Product range FuseBasic function Fuse-linkField of application high speedRated current [I]
175 ARated voltage AC 500 V DC 500 VSize 29 x 92 mmUtilization category aRStatus indicator with indicatorBreaking Capacity 200 kA
Usable for size/applications DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval ULShape cylindrical with centre-bolted tagsStandards/Regulations UL 248
Technical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeOtherRated current175 ARated voltage500 VVoltage typeAC/DCRated switching
capacity200 kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorOtherInsulated
metal gripping lugs (IMGL)No
ETIM for FWH-175BI Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC/DC
Rate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / S/COND FUSE WITH IND. 175A 500V with the required quantity to info@electricaonline.com or
use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.