

INDUSTRIAL COMPONENT DATA

S811+U36P3S 169872 Y7-169872 EATON ELECTRIC Soft starter, 361 A, 200 600 V AC, Us 24 V DC, with control unit..

Brand: EATON - MOELLER | Manufacturer Part Number: S811+U36P3S



Manufacturer	EATON - MOELLER
MPN / Reference	S811+U36P3S
Catalog number	Y7-169872
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-48781D1BDF
Generated	2026-08-03

Product Overview

Soft starter, 361 A, 200 - 600 V AC, Us= 24 V DC, with control unit and pump algorithm, Frame size U
S811+U36P3S

Soft starter, Description: With internal bypass contacts, Function: Soft starter for three-phase loads, with control unit and pump algorithm, Mains supply voltage (50/60 Hz): ULN= 200 - 600 V AC, Supply voltage: Us= 24 V DC, Control voltage: UC= 24 V DC, Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz: P= 200 kW, at 460 V, 60 Hz: P= 300 HP, Rated operational current AC-53: Ie= 361 A, Rated operational current AC-53, In-Delta: Ie= 623 A, Startup class: CLASS 10 (star-delta replacement), CLASS 20 (heavy starting duty 3 x Ie for 45 s), CLASS 30 (6 x Ie for 30 s), Rated operational voltage: Ue= 200 V, 230 V, 400 V, 480 V, 600 V, Connection to SmartWire-DT: no, Frame size: U, Ordering information: Terminal blocks for the terminals are required for frame sizes T, U, and V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > High Performance Soft Starters
--------------	--

Additional Product Information

General specifications

Product Name Eaton S811 Soft starter Catalog Number 169872 Model Code S811+U36P3S EAN 4015081663699 Product Length/Depth 182 mm Product Height 323.1 mm Product Width 194.4 mm Product Weight 18.6 kg Certifications

CSA22.2-14-1995

CSA File No.: LR 353

UL 508

CCC

UL
UL File No.: E202571
CSA-C22.2 No. 14
IEC/EN 60947-4-2
C-Tick
CSA
CSA Class No.: 3211-06
CE
GB14048
UL Category Control No.: NMFT Features & Functions
Fault memory 10 Faults Fitted with: Internal bypass
Display
Internal bypass contacts
Motor overload protection Functions Min. ramp time 1 s - fast switching (semiconductor contactor)
Suppression of closing transients
Underload monitoring
Single direction
Potential isolation between power and control sections
Soft start function
Overload monitoring
Suppression of DC components for motors
Current limitation Interfaces Modbus RTU (built-in) General
Class Adjustable Connection to SmartWire-DT No Degree of protection IP00
NEMA Other Frame size U Mains voltage - min 200 V Mains voltage - max 600 V Mounting position As required
Overvoltage category II Pollution degree 3 Radio interference class Class A (EN 55011) Rated impulse withstand voltage (Uimp) 4000 V Rated insulation voltage (Ui) 660 V Shock resistance 15 g, Mechanical Startup class CLASS 10 (star-delta replacement)
CLASS 30 (6 x Ie for 30 s)
CLASS 20 (heavy starting duty 3 x Ie for 45 s) Suitable for Branch circuits, not as BCPD, (UL/CSA) Type Soft starter for three-phase loads, with control u...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / S811+U36P3S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.