

INDUSTRIAL COMPONENT DATA

S811+U42N3S 169870 S811PLUSU42N3S EATON ELECTRIC
Soft starter, 420 A, 200 600 V AC, Us 24 V DC, Frame size U

Brand: EATON - MOELLER | Manufacturer Part Number: S811+U42N3S



Manufacturer	EATON - MOELLER
MPN / Reference	S811+U42N3S
Catalog number	S811PLUSU42N3S
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-776BD9D2F2
Generated	2026-08-05

Product Overview

Soft starter, 420 A, 200 - 600 V AC, Us= 24 V DC, Frame size U

Soft starter, 420 A, 200 - 600 V AC, Us= 24 V DC, with control unit, Frame size U

Soft starter, Description: With internal bypass contacts, Function: Soft starter for three-phase loads, with control unit, Mains supply voltage (50/60 Hz): ULN= 200 - 600 V AC, Supply voltage: Us= 24 V DC, Control voltage: UC= 24 V DC, Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz: P= 200 kW, at 460 V, 60 Hz: P= 350 HP, Rated operational current AC-53: Ie= 420 A, Rated operational current AC-53, In-Delta: Ie= 727 A, Startup class: CLASS 10 (star-delta replacement), CLASS 20 (heavy starting duty 3 x Ie for 45 s), CLASS 30 (6 x Ie for 30 s), Rated operational voltage: Ue= 200 V, 230 V, 400 V, 480 V, 600 V, Connection to SmartWire-DT: no, Frame size: U, Ordering information: Terminal blocks for the terminals are required for frame sizes T, U, and V -> Accessories, Standards: IEC/EN 60947-4-2, UL 508, CSA22.2-14-1995, GB14048

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > High Performance Soft Starters

Additional Product Information

General specifications

Product Name Eaton S811 Soft starter Catalog Number 169870 Model Code S811+U42N3S EAN 4015081663682 Product Length/Depth 182 mm Product Height 323.1 mm Product Width 194.4 mm Product Weight 18.6 kg Certifications CSA File No.: LR 353

UL Category Control No.: NMFT

UL File No.: E202571

CE
UL 508
CSA Class No.: 3211-06
CSA
UL
GB14048
CSA22.2-14-1995
CSA-C22.2 No. 14
C-Tick
CCC
IEC/EN 60947-4-2 Features & Functions
Fault memory 10 Faults Fitted with: Display
Internal bypass
Motor overload protection
Internal bypass contacts Functions Suppression of closing transients
Soft start function
Suppression of DC components for motors
Min. ramp time 1 s - fast switching (semiconductor contactor)
Potential isolation between power and control sections
Overload monitoring
Current limitation
Underload monitoring
Single direction Interfaces Modbus RTU (built-in) General
Class Adjustable Connection to SmartWire-DT No Degree of protection IP20
NEMA Other Frame size U Mains voltage - min 200 V Mains voltage - max 600 V Mounting position As required
Overvoltage category II Pollution degree 3 Radio interference class Class A (EN 55011) Rated impulse withstand voltage (Uimp) 4000 V Rated insulation voltage (Ui) 660 V Shock resistance 15 g, Mechanical Startup class CLASS 10 (star-delta replacement)
CLASS 20 (heavy starting duty 3 x Ie for 45 s)
CLASS 30 (6 x Ie for 30 s) Suitable for Branch circuits, not as BCPD, (UL/CSA) Type Soft starter for three-phase loads, with control u...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / S811+U42N3S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.