

INDUSTRIAL COMPONENT DATA

LS4/S11-S//ZB/X 114291 LS4-S11-S-I-ZB-X EATON ELECTRIC

Safety position switch, 1N/O+1N/C, without actuator

Brand: EATON - MOELLER | Manufacturer Part Number: LS4/S11-S//ZB/X



Manufacturer	EATON - MOELLER
MPN / Reference	LS4/S11-S//ZB/X
Catalog number	LS4-S11-S-I-ZB-X
Category	End switch
Minimum order	1 Pcs
Document ID	EO-6B3FC9A406
Generated	2026-08-06

Product Overview

Safety position switch, 1N/O+1N/C, without actuator

LS4/S11-S//ZB/X

Safety position switch, LS(4)...ZB, Safety position switches, 1 N/O, 1 NC, narrow, Snap-action contact - Yes, Screw terminal

IEC EN 60947-5-1, IP65_x, robust type, approval of employers' liability insurance Association GS-ET-15, device for world markets, safety position switch for protection of personnel with separated actuator for protective shrouds, positive operation, and positive-opening contacts, suitable for use with electronic devices to IEC/EN 61131-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

Safety position switch, LS(4)...ZB, Safety position switches, 1 N/O, 1 NC, narrow, Snap-action contact - Yes, Screw terminal IEC EN 60947-5-1, IP65_x, robust type, approval of employers' liability insurance Association GS-ET-15, device for world markets, safety position switch for protection of personnel with separated actuator for protective shrouds, positive operation, and positive-opening contacts, suitable for use with electronic devices to IEC/EN 61131-2 Delivery program Basic function Position switches

Safety position switches Part group reference LS(4)...ZB Product range Safety position switches Degree of Protection IP65 Snap-action contact Yes Description With the actuator inserted, the N/O contact is open and the NC contact is closed. Contacts N/O = Normally open 1 N/O N/C = Normally closed 1 NC Notes = safety function, by positive opening to IEC/EN 60947-5-1 Connection type Screw terminal Technical data

General Standards IEC/EN 60947 Climatic proofing Damp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC 60068-2-30 Mounting position As required Degree of Protection IP65 Terminal capacitiesSolid 1 x (0.75 - 2.5) 2 x (0.75 - 1.5) mm² Terminal capacitiesFlexible with ferrule 1 x (0.5 - 1.5) 2 x (0.5 - 1.5) mm² Terminal screw PH1 Repetition accuracy 0.02 mm Contacts/switching capacity Rated impulse withstand voltage [Uimp] 6000 V AC Rated insulation voltage [Ui] 500 V Overvoltage category/pollution degree III/3 Rated operational current [Ie]AC-1524 V [Ie] 6 A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LS4/S11-S/II/ZB/X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.