

INDUSTRIAL COMPONENT DATA

LS4/S12-7/IB/ZB 106859 EATON ELECTRIC Safety position switch, 1N/O+2N/C, insulated material, + actuator ZB

Brand: EATON - MOELLER | Manufacturer Part Number: LS4/S12-7/IB/ZB



Manufacturer	EATON - MOELLER
MPN / Reference	LS4/S12-7/IB/ZB
Catalog number	106859
Category	End switch
Minimum order	1 Pcs
Document ID	EO-23C395E98C
Generated	2026-08-06

Product Overview

Safety position switch, 1N/O+2N/C, insulated material, + actuator ZB

LS4/S12-7/IB/ZB

Safety position switch, LS(4)...ZB, Safety position switches, Complete unit, 1 N/O, 2 NC, Insulated material, Screw terminal, -25 - +70 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

Safety position switch, LS(4)...ZB, Safety position switches, Complete unit, 1 N/O, 2 NC, Insulated material, Screw terminal, -25 - +70 °C Safety position switch, Basic function: Position switches, Safety position switches, Part group reference: LS(4)...ZB, Product range: Safety position switches, Degree of Protection: IP65, Features: Complete unit, Ambient temperature: -25 - +70 °C, Description: With the actuator inserted, the N/O contact is open and the NC contact is closed., Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 2 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947 Delivery program

Basic function Position switches

Safety position switches Part group reference LS(4)...ZB Product range Safety position switches Degree of Protection IP65 Features Complete unit Ambient temperature -25 - +70 °C Description With the actuator inserted, the N/O contact is open and the NC contact is closed. Approval Contacts N/O = Normally open 1 N/O N/C = Normally closed 2 NC Notes = safety function, by positive opening to IEC/EN 60947-5-1 Contact sequence Contact travel? = Contact closed? = Contact open

Housing Insulated material Connection type Screw terminal Notes Do not, under any circumstance, use the switch as a mechanical stop or transportation restraint or brace!

Connect operating elements permanently with the protective device, e.g., with non-reusable screws or...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LS4/S12-7/IB/ZB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.