

INDUSTRIAL COMPONENT DATA

LSM-11/L 266145 Y7-266145 EATON ELECTRIC Safety position switch, metal, 1N/O+1N/C, roller lever

Brand: EATON - MOELLER | Manufacturer Part Number: LSM-11/L



Manufacturer	EATON - MOELLER
MPN / Reference	LSM-11/L
Catalog number	Y7-266145
Category	End switch
Minimum order	2 Pcs
Document ID	EO-E50454609C
Generated	2026-08-05

Product Overview

Safety position switch, metal, 1N/O+1N/C, roller lever

LSM-11/L

Eaton Moeller® series LSM Safety position switch, metal, 1N/O+1N/C, roller lever LSM-11/L

Safety position switch, Basic function: Position switches, Safety position switches, Part group reference: LS(M)-..., Product range: Roller lever, Degree of Protection: IP66, IP67, Features: Complete unit, Ambient temperature: -25 - +70 °C, Design: EN 50047 Form E, Description: Long, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Positive opening (ZW): yes, Color Enclosure covers: Yellow, Housing: Metal, Connection type: Cage Clamp, Cage-Clamp is a registered trademark of Wago Kontakttechnik, 32432 Minden, Germany. , Accessories for the Cage-Clamp terminals from Wago:power comb, gray, Wago Article No. 264-402, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series LSM Safety position switch Catalog Number 266145 Model Code LSM-11/L EAN 4015082661458 Product Length/Depth 33.5 mm Product Height 96 mm Product Width 31 mm Product Weight 0.167 kg

Certifications CSA File No.: 012528

IEC/EN 60947

UL File No.: E29184

CSA-C22.2 No. 14

CE

CSA Class No.: 3211-03

CSA

UL Category Control No.: NKCR

IEC/EN 60947-5

UL

UL 508 Catalog Notes The operating head can be rotated 90° to enable adaptation to the specified approach direction

Features & Functions

Design EN 50047 Form E Electric connection type Cable entry metrical Enclosure color Yellow Cover Enclosure material

Metal Features Forced opening

Positive opening Switch function type Slow-action switch General

Connection type Cage Clamp Degree of protection IP66/IP67

NEMA Other Operating frequency 6000 Operations/h Overvoltage category III Pollution degree 3 Product category Roller lever Rated impulse withstand voltage (Uimp) 4000 V AC Repetition accuracy 0.15 mm (Contacts/switching capacity)

Suitable for Safety functions Type Safety position switch Ambient conditions, mechanical

Mounting position As required Shock resistance 25 g, Standard-action contact, Mechanical, Half-sinusoidal shock 20 ms

Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Terminal capacities

Terminal capacity (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LSM-11/L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.