

INDUSTRIAL COMPONENT DATA

P3-63/I4-SI-SW 207362 Y7-207362 EATON ELECTRIC safety switch, 3p, 63 A, Emergency stop function, Lockable in..

Brand: EATON - MOELLER | Manufacturer Part Number: P3-63/I4-SI-SW



Manufacturer	EATON - MOELLER
MPN / Reference	P3-63/I4-SI-SW
Catalog number	Y7-207362
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-0DD2805459
Generated	2026-08-04

Product Overview

safety switch, 3p, 63 A, Emergency stop function, Lockable in position 0 with cover interlock, surface mounting, with warning label „safety switch”

P3-63/I4-SI-SW

Eaton Moeller® series P3 Safety switch, P3, 63 A, 3 pole, STOP function, With black rotary handle and locking ring, Lockable in position 0 with cover interlock, with warning label „safety switch”

Safety switch, Product range: safety switch, Part group reference: P3, Stop Function: STOP function, With black rotary handle and locking ring, Notes: with warning label „safety switch”, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Locking facility: Lockable in position 0 with cover interlock, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series P3 Accessory Insulated enclosure Catalog Number 207362 Model Code

P3-63/I4-SI-SW EAN 4015082073626 Product Length/Depth 139 mm Product Height 180 mm Product Width 160 mm

Product Weight 1.002 kg Certifications EN 60204

EN 60947

IEC 60947

VDE

IEC/EN 60204

IEC/EN 60947

IEC/EN 60947-3

VDE 0660 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 207362 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

Yes

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current I_u (EF001389)

63 A

Rated permanent current at AC-23, 400 V (EF011777)

63 A

Rated permanent current at AC-21, 400 V (EF009165)

63 A

Rated operation power at AC-3, 400 V (EF001364)

30 kW

Rated short-time withstand current I_{cw} (EF007050)

1.26 kA

Rated operation power at AC-23, 400 V (EF007027)

30 kW

Switching power at 400 V (EF009166)

30 kW

Conditioned rated short-circuit current I_q (EF001444)

100 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-63/I4-SI-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.