

INDUSTRIAL COMPONENT DATA

Eaton 9PX 5000i HotSwap 9PX5KIBP EATON ELECTRIC Eaton 9PX 5000i HotSwap

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 5000i HotSwap



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 5000i HotSwap
Catalog number	9PX5KIBP
Category	UPS
Minimum order	1 Pcs
Document ID	EO-0A45F9180D
Generated	2026-08-05

Product Overview

Eaton 9PX 5000i HotSwap

Eaton 9PX UPS, 5000 VA, 4500 W, Input: Hardwired, Outputs: (3) C13, (2) C19, Hardwired, Rack/tower, 3U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General specifications

Product Name Eaton 9PX UPS Catalog Number 9PX5KIBP Model Code Eaton 9PX 5000i HotSwap UPC 743172040534
Product Length/Depth 68.5 cm Product Height 44 cm Product Width 13 cm Product Weight 48 kg Compliances CE Marked
TUV

cULus Listed

CSA 22.2 Certifications UL 1778

IEC/EN 62040-1

IEC/EN 62040-2

CE

EAC Battery

Runtime graph View runtime graph Battery management Battery replacement Hot-swappable internal batteries and
extended battery modules (EBMs) Battery quantity 15 Battery rating 12 V / 5 Ah Battery type Sealed, lead-acid Extended
battery capability Yes Electrical output

Receptacle (3) C13, (2) C19, Hardwired Topology Online/Double-conversion Wattage 4500 W VA rating 5000 VA Output

waveform Sine wave Voltage 230V Output power factor 0.9 Output nominal voltage 230V default (200/208/220/230/240V)
Output voltage range 200/208/220/230/240 V +/- 1% Voltage distortion output (linear load) - max 2 Output frequency 50/60
Hz Feed type 1 Electrical input
Input connection Hardwired/fixed connection Input nominal voltage 230V default (200/208/220/230/240V) Input voltage
range 176-276 V (100-276 V with derating) Nominal frequency 50/60 Hz Input frequency range 40-70 Hz Input power factor
>.99 Communications
Communication USB port (HID compliant)
Serial port (RS232)
Mini terminal block for remote On/Off
Mini-terminal block for remote power off
Dry contacts (4 outputs, relay, DB9)
DB15 for parallel operation
Expansion slots One slot for optional communication card E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 5000i HotSwap with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.