

INDUSTRIAL COMPONENT DATA

Eaton 9SX 11000i RT6U 9SX11KIRT EATON ELECTRIC Eaton 9SX 11000i RT6U (con kit rack)

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9SX 11000i RT6U



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9SX 11000i RT6U
Catalog number	9SX11KIRT
Category	UPS
Minimum order	1 Pcs
Document ID	EO-1B00DC3A06
Generated	2026-08-04

Product Overview

Eaton 9SX 11000i RT6U (con kit rack)

Eaton 9SX 11000i RT6U

Eaton 9SX UPS, 11 kVA, 10 kW, Input: Hardwired, Outputs: Hardwired, Rack/tower, 6U, Rack-mounting kit included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General specifications

Product Name Eaton 9SX UPS Catalog Number 9SX11KIRT Model Code Eaton 9SX 11000i RT6U UPC 743172040237

Product Length/Depth 70 cm Product Height 26 cm Product Width 44 cm Product Weight 79 kg Compliances CE Marked

TUV Certifications IEC/EN 62040-1

IEC/EN 62040-2

CE

EAC Battery

Battery type Sealed, lead-acid Runtime graph View runtime graph Battery replacement Hot-swappable battery modules

Battery quantity 20 Battery management Battery rating 12 V / 7 Ah Extended battery capability Yes Electrical output

Receptacle Hardwired Voltage 230V Wattage 10 kW Output power factor 0.9 Output voltage range

200/208/220/230/240/250 V +/- 1% Output waveform Sine wave Output nominal voltage 230V default

(200/208/220/230/240/250V) Voltage distortion output (linear load) - max 2 Feed type 1 Topology Online/Double-conversion

VA rating 11 kVA Electrical input

Input connection Hardwired/fixed connection Input nominal voltage 230V default (200/208/220/230/240/250V) Nominal frequency 50/60 Hz Input power factor >.99 Input voltage range 176-276 V (100-276 V with derating) Input frequency range 40-70 Hz Communications
Includes network card No Communication USB port (HID compliant)
Serial port (RS232)
Mini terminal block for remote On/Off
Mini-terminal block for remote power off
Dry contacts (4 outputs, relay, DB9)
Ethernet interface No User interface Multilingual graphical LCD display Potential free switch contact Yes Expansion slots
One slot for optional communication card Soft...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9SX 11000i RT6U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.