

INDUSTRIAL COMPONENT DATA

Eaton 9SX 6000i RT3U 9SX6KIRT 9104-12567 EATON ELECTRIC Eaton 9SX 6000i RT3U (con kit rack)

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9SX 6000i RT3U



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9SX 6000i RT3U
Catalog number	9104-12567
Category	UPS
Minimum order	1 Pcs
Document ID	EO-85B3092DC1
Generated	2026-08-03

Product Overview

Eaton 9SX 6000i RT3U (con kit rack)

Eaton 9SX 6000i RT3U

Eaton 9SX UPS, 6000 VA, 5400 W, Input: Hardwired, Outputs: (8) C13, (2) C19, Hardwired, Rack/tower, 3U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General specifications

Product Name Eaton 9SX UPS Catalog Number 9SX6KIRT UPC 743172039354 Product Length/Depth 68.5 cm Product Height 13 cm Product Width 44 cm Product Weight 48 kg Compliances CE Marked

TUV

cULus Listed

CSA 22.2 Certifications IEC/EN 62040-1

UL 1778

IEC/EN 62040-2

CE

cULus Listed

EAC Battery

Battery type Sealed, lead-acid Runtime graph View runtime graph Battery replacement Hot-swappable internal batteries and extended battery modules (EBMs) Battery quantity 15 Battery management Battery rating 12 V / 5 Ah Extended battery

capability Yes Electrical output

Receptacle (8) C13, (2) C19, Hardwired Voltage 230V Wattage 5400 W Output power factor 0.9 Output voltage range 200/208/220/230/240 V +/- 1% Output waveform Sine wave Output nominal voltage 230V default (200/208/220/230/240V) Voltage distortion output (linear load) - max 2 Feed type 1 Topology Online/Double-conversion VA rating 6000 VA Electrical input

Input connection Hardwired/fixed connection Input nominal voltage 230V default (200/208/220/230/240/250V) Nominal frequency 50/60 Hz Input power factor >.99 Input voltage range 176-276 V (100-276 V with derating) Input frequency range 40-70 Hz Communications

Includes network card No Communication USB port (HID compliant)

Serial port (RS232)

Mini terminal block for remote On/Off

Mini-terminal block for remote power off

Dry contacts (4 outputs, relay, DB9)

Ethernet interface No User interface Multilingual graphical LCD display Potential free switch contact Yes...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9SX 6000i RT3U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.