

INDUSTRIAL COMPONENT DATA

BUSS SC FUSE CLASS G CLASS G SC-3 EATON ELECTRIC

Fuse-link, low voltage, 10 A, AC 600 V, DC 170 V, 33.3 x 10..

Brand: EATON - MOELLER | Manufacturer Part Number: BUSS SC FUSE CLASS G CLASS G



Manufacturer	EATON - MOELLER
MPN / Reference	BUSS SC FUSE CLASS G CLASS G
Catalog number	SC-3
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-367A4757C9
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 10 A, AC 600 V, DC 170 V, 33.3 x 10.4 mm, G, UL, CSA, time-delay

BUSS SC FUSE CLASS G CLASS G

BUSS SC FUSE CLASS G CLASS G - Fuse-link, low voltage, 3 A, AC 600 V, DC 170 V, 100 kA, 33.3 x 10.4 mm, G, UL, CSA, size-rejecting, fast-acting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

Fuse-link, low voltage, 3 A, AC 600 V, DC 170 V, 100 kA, 33.3 x 10.4 mm, G, UL, CSA, size-rejecting, fast-acting
Fuse-link, low voltage, 3 A, AC 600 V, DC 170 V, 33.3 x 10.4 mm, G, UL, CSA, fast-acting, cylindrical, size-rejecting, fusible
branch panelboards, HVAC branch circuit protection, UL 248-5, Breaking Capacity 100 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application low voltage
Rated current [I] 3 A
Rated voltage AC 600 V
DC 170 V
Size 33.3 x 10.4 mm
Utilization category G
Description size-rejecting
Breaking Capacity 100 kA
Usable for size/applications fusible branch panelboards, HVAC branch circuit protection
Release characteristic

[class] fast-acting
Standard/Approval UL

CSA Shape cylindrical
Standards/Regulations UL 248-5
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ()
[AFZ797013])
Size Other
Rated voltage 600 - 600 V
Rated voltage Other
Voltage type AC/DC
Utilization category Other
Rated operating frequency 45 - 62 Hz
Nominal current 3 A
With striker No
Release characteristic GB
Breaking capacity 100 kA

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BUSS SC FUSE CLASS G CLASS G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.