

INDUSTRIAL COMPONENT DATA

BUSS SC FUSE CLASS G CLASS G SC-45 EATON ELECTRIC

Fuse-link, low voltage, 10 A, AC 600 V, DC 170 V, 33.3 x 1..

Brand: EATON - MOELLER | Manufacturer Part Number: BUSS SC FUSE CLASS G CLASS G



Manufacturer	EATON - MOELLER
MPN / Reference	BUSS SC FUSE CLASS G CLASS G
Catalog number	SC-45
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-48BF1F0F42
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 10 A, AC 600 V, DC 170 V, 33.3 x 10.4 mm, G, UL, CSA, time-delay

BUSS SC FUSE CLASS G CLASS G

BUSS SC FUSE CLASS G CLASS G - Fuse-link, low voltage, 45 A, AC 480 V, DC 300 V, 100 kA, 57.1 x 10.4 mm, G, UL, CSA, size-rejecting, time-delay

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

Fuse-link, low voltage, 45 A, AC 480 V, DC 300 V, 100 kA, 57.1 x 10.4 mm, G, UL, CSA, size-rejecting, time-delay
Fuse-link, low voltage, 45 A, AC 480 V, DC 300 V, 57.1 x 10.4 mm, G, UL, CSA, time-delay, cylindrical, size-rejecting, fusible branch panelboards, HVAC branch circuit protection, UL 248-5, Breaking Capacity 100 kA, time-delay 12 seconds (minimum) at 200% of rated current
Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 45 A Rated voltage AC 480 V DC 300 V Size 57.1 x 10.4 mm Utilization category G Descriptions size-rejecting Breaking Capacity 100 kA usable for size/applications fusible branch panelboards, HVAC branch circuit protection Release characteristic [class] time-delay Standard/Approval UL

CSA Shape cylindrical Standards/Regulations UL 248-5 Time delay time-delay 12 seconds (minimum) at 200% of rated current Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ()

[AFZ797013])SizeOtherRated voltage480 - 480 VRated voltageOtherVoltage typeACUtilization categoryOtherRated operating frequency45 - 62 HzNominal current45 AWith strikerNoRelease characteristicGBreaking capacity100 kA

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BUSS SC FUSE CLASS G CLASS G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.