

INDUSTRIAL COMPONENT DATA

BUSS SC FUSE CLASS G CLASS G SC-5 EATON ELECTRIC

Fuse-link, low voltage, 10 A, AC 600 V, DC 170 V, 33.3 x 10..

Brand: EATON - MOELLER | Manufacturer Part Number: BUSS SC FUSE CLASS G CLASS G



Manufacturer	EATON - MOELLER
MPN / Reference	BUSS SC FUSE CLASS G CLASS G
Catalog number	SC-5
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-73F146BDD2
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 10 A, AC 600 V, DC 170 V, 33.3 x 10.4 mm, G, UL, CSA, time-delay

BUSS SC FUSE CLASS G CLASS G

BUSS SC FUSE CLASS G CLASS G - Fuse-link, low voltage, 5 A, AC 600 V, DC 170 V, 100 kA, 33.3 x 10.4 mm, G, UL, CSA, size-rejecting, fast-acting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

Fuse-link, low voltage, 5 A, AC 600 V, DC 170 V, 100 kA, 33.3 x 10.4 mm, G, UL, CSA, size-rejecting, fast-acting Fuse, Fuse-link, low voltage, 5 A, AC 600 V, DC 170 V, 33.3 x 10.4 mm, G, UL, CSA, fast-acting, cylindrical, size-rejecting, fusible branch panelboards, HVAC branch circuit protection, UL 248-5, Breaking Capacity 100 kA Delivery program Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 5 A Rated voltage AC 600 V DC 170 V Size 33.3 x 10.4 mm Utilization category G Description size-rejecting Breaking Capacity 100 kA Usable for size/applications fusible branch panelboards, HVAC branch circuit protection Release characteristic [class] fast-acting Standard/Approval UL CSAShape cylindrical Standards/Regulations UL 248-5 Technical data ETIM 7.0 Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) () [AFZ797013]) Size Other Rated voltage 600 - 600 V Rated voltage Other Voltage type AC/DC Utilization category Other Rated operating frequency 45 - 62 Hz Nominal current 5 A With striker No Release characteristic GB Breaking capacity 100 kA

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BUSS SC FUSE CLASS G CLASS G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.