

INDUSTRIAL COMPONENT DATA

NZM2-XKS 260030 Y7-260030 EATON ELECTRIC Screw connection 3p, standard, size 2

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2-XKS



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2-XKS
Catalog number	Y7-260030
Category	Wiring set for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-4B86917A5E
Generated	2026-08-02

Product Overview

Screw connection 3p, standard, size 2

NZM2-XKS

Eaton Moeller series NZM - Molded Case Circuit Breaker. Screw connection 3p, standard, size 2

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: part no. contains parts for a terminal located at top or bottom for 3 or 4 pole switches. Standard connection with all NZM2, PN2 and N2 circuit-breakers. Conversion kit for circuit-breaker with box terminal. Use special cable lug narrow version. fitted within the switch housing. If a busbar is used, insulation (400 mm) e.g sleeving and a NZM2(4)-XKSA cover are required. U e ? 525 VAC . For all other connection material e.g. cables, flat conductors, a NZM2(-4)-XKSA shroud must be used. Can be used for: NZM2(-4), PN2(-4), N(N/O)2(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM connection type Catalog Number 260030 Model Code NZM2-XKS EAN

4015082600303 Product Length/Depth 103 mm Product Height 336 mm Product Width 105 mm Product Weight 0.064 kg

Compliances UL/CSA

IEC

RoHS conform Certifications UL listed

CSA (Class No. 1432-01)

CSA certified

UL489

UL (Category Control Number DIHS)

CE marking

CSA (File No. 22086)

CSA-C22.2 No. 5-09

UL (File No. E31593)

IEC60947 Product specifications

Used with NZM2, PN2, N(S)2 Type AccessoryScrew connectionTerminal Amperage Rating 300 A (Cu), 250 A (Al) 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the pro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2-XKS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.