


INDUSTRIAL COMPONENT DATA

**SDAINLM165(110V50HZ,120V60HZ) 240032 Y7-240032 EATON
ELECTRIC Star-delta contactor combination, 3p, 90kW/400..**

Brand: EATON - MOELLER | Manufacturer Part Number: SDAINLM165(110V50HZ,120V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	SDAINLM165(110V50HZ,120V60HZ)
Catalog number	Y7-240032
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-B8DDD1631A
Generated	2026-08-06

Product Overview

Star-delta contactor combination, 3p, 90kW/400V/AC3

SDAINLM165(110V50HZ,120V60HZ)

Eaton Moeller® series SDAINL Star-delta contactor combination, 380 V 400 V: 90 kW, 110 V 50 Hz, 120 V 60 Hz, AC operation

Star-delta contactor combination, Application: Star-delta motor starting for contactor combinations, Operating frequency: maximum 30 starts per hour, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, Rated operational current AC-3 380 V 400 V: I_e= 165 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 45 kW, 380 V 400 V: P= 90 kW, 500 V: P= 110 kW, 660 V 690 V: P= 132 kW, Max. changeover time: 20 s, Actuating voltage: 110 V 50 Hz, 120 V 60 Hz, Voltage AC/DC: AC operation, Individual components of the combination Mains contactor Q11: DILM95, + DILM150-XHI11 , Delta contactor Q15: DILM95, + DILM150-XHI31 Part no., Star contactor Q13: DILM65, + DILM150-XHI11 Part no., Timing relay K1: ETR4-51 Part no., Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series SDAINL contactor combination Catalog Number 240032 Model Code

SDAINLM165(110V50HZ,120V60HZ) EAN 4015082400323 Product Length/Depth 183 mm Product Height 314 mm

Product Width 308 mm Product Weight 9.6 kg Certifications CE Features & Functions

Functions Star-delta contactor Number Of Poles Three-pole General

Application Star-delta motor starting for contactor combinations Overvoltage category III Pollution degree 3 Product category Contactor combinations Suitable for Also motors with efficiency class IE3 Used with ETR4-51 Utilization category AC-3: Normal AC induction motors: starting, switch off during running Voltage type AC Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min -25 °C Ambient operating temperature (enclosed) - max 40 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 80 °C Electro Magnetic Compatibility Interference immunity According to EN 60947-1 Electrical Rating Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 165 A Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V 165 A Rated insulation voltage (Ui) 690 V Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 165 A Rated operational power at AC-3, 380/400 V, 50 Hz 90 kW Switching time Changeover time 20 s, max. Magnet system Duty factor 100 % Rated control supply voltage (Us) at AC, 5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SDAINLM165(110V50HZ,120V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.