


INDUSTRIAL COMPONENT DATA

SDAINLM45(400V50HZ) 101384 Y7-101384 EATON ELECTRIC Star-delta contactor combination, 22kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: SDAINLM45(400V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	SDAINLM45(400V50HZ)
Catalog number	Y7-101384
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-BD8322DBFC
Generated	2026-08-06

Product Overview

Star-delta contactor combination, 22kW/400V/AC3

SDAINLM45(400V50HZ)

Eaton Moeller® series SDAINL Star-delta contactor combination, 380 V 400 V: 22 kW, 400 V 50 Hz, AC operation

Star-delta contactor combination, Application: Star-delta motor starting for contactor combinations, Operating frequency: maximum 30 starts per hour, Accessories: Star-delta combinations SDAINL, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, Rated operational current AC-3 380 V 400 V: I_e = 45 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 11 kW, 380 V 400 V: P = 22 kW, 500 V: P = 30 kW, 660 V 690 V: P = 22 kW, Max. changeover time: 20 s, Actuating voltage: 400 V 50 Hz, Voltage AC/DC: AC operation, Individual components of the combination Mains contactor Q11: DILM25-10, + DILA-XHI20, Delta contactor Q15: DILM25-01, + DILA-XHI20 Part no., Star contactor Q13: DILM17-01, + DILA-XHI20 Part no., Timing relay K1: ETR4-51 Part no., Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series SDAINL contactor combination Catalog Number 101384 Model Code

SDAINLM45(400V50HZ) EAN 4015081011278 Product Length/Depth 138 mm Product Height 95 mm Product Width 158 mm Product Weight 1.61 kg Certifications CE Features & Functions

Functions Star-delta contactor Number Of Poles Three-pole General

Application Star-delta motor starting for contactor combinations Overvoltage category III Pollution degree 3 Product category Contactor combinations Suitable for Also motors with efficiency class IE3 Used with ETR4-51 Utilization category AC-3: Normal AC induction motors: starting, switch off during running Voltage type AC Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min -25 °C Ambient operating temperature (enclosed) - max 40 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 80 °C Electro Magnetic Compatibility Interference immunity According to EN 60947-1 Electrical Rating Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 45 A Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V 45 A Rated insulation voltage (Ui) 690 V Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 45 A Rated operational power at AC-3, 380/400 V, 50 Hz 22 kW Switching time Changeover time 20 s, max. Magnet system Duty factor 100 % Rated control supply voltage (Us) at AC, 50 Hz - min 40...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SDAINLM45(400V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.