

INDUSTRIAL COMPONENT DATA

NZMH3-VE400-S1 119367 Y7-119367 EATON ELECTRIC

Circuit-breaker, 3p, 400A, 1000 V

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH3-VE400-S1



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH3-VE400-S1
Catalog number	Y7-119367
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-DC191FA688
Generated	2026-08-02

Product Overview

Circuit-breaker, 3p, 400A, 1000 V

NZMH3-VE400-S1

Circuit-breaker NZM3, 3 pole, Switching capacity 1000 V 50/60 Hz(Ics): 15 kA, Rated current = rated uninterrupted current(In = Iu): 400 A, Installation type: Fixed, Screw connection, Standard/Approval: IEC, Protective function: Systems, cable, selectivity and generator protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

Circuit-breaker, 3p, 400A, 1000 V Circuit-breaker NZM3, 3 pole, Switching capacity 1000 V 50/60 Hz(Ics): 15 kA, Rated current = rated uninterrupted current(In = Iu): 400 A, Installation type: Fixed, Screw connection, Standard/Approval: IEC, Protective function: Systems, cable, selectivity and generator protection

General specifications
Product name Eaton Moeller series NZM molded case circuit breaker electronic
Part no. NZMH3-VE400-S1 EAN4015081175031
Product Length/Depth 166 millimetre
Product height 275 millimetre
Product width 140 millimetre
Product weight 6.34 kilogram
Compliances RoHS conform
Certifications IEC
Product Tradename NZM
Product Type Molded case circuit breaker
Product Sub Type Electronic
Delivery program Type Circuit breaker
Circuit breaker frame type NZM3
Number of poles Three-pole
Amperage Rating 400 A
Release system Electronic
release Features Motor drive optional

Protection unit Special features Lifespan, mechanical: of which max. 50 % trip by shunt/undervoltage release
R.m.s. value measurement and "thermal memory"
Adjustable time delay setting to overcome current peaks tr at 6 x I_r also infinity (without

overload releases)Adjustable delay time tsd: Steps: 0, 20, 60, 100, 200, 300, 500, 750, 1000 msi²t constant function:
switchableNZM4...S1 terminal type: Insulated busbar connection (NZM4-XKS screw connection)Rated current = rated
uninterrupted current: 400 ATerminal capacity hint: Up to 240 mm² can be connected depending on the cable
manufacturer.Technical Data - ElectricalVoltage rating100...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH3-VE400-S1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.