

INDUSTRIAL COMPONENT DATA

M22-WRK3/K20 216520 Y7-216520 EATON ELECTRIC Selector switch, 2N/O, 3 positions, front mount

Brand: EATON - MOELLER | Manufacturer Part Number: M22-WRK3/K20



Manufacturer	EATON - MOELLER
MPN / Reference	M22-WRK3/K20
Catalog number	Y7-216520
Category	Selector switch, complete
Minimum order	5 Pcs
Document ID	EO-8880623265
Generated	2026-08-03

Product Overview

Selector switch, 2N/O, 3 positions, front mount

M22-WRK3/K20

Eaton Moeller® series M22 Changeover switch, RMQ-Titan, With thumb-grip, maintained, 3 positions, 2 N/O, Bezel: titanium

Changeover switch, Product range: RMQ-Titan, Complete unit, Design: With thumb-grip, maintained, Screw connection, 3 positions, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: no, Front dimensions: 29,7, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Contactor states 0, I and II correspond with the position of the actuator as viewed from the front., Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Selector switch Catalog Number 216520 Model Code M22-WRK3/K20 EAN 4015082165208 Product Length/Depth 130 mm Product Height 30 mm Product Width 30 mm Product Weight 0.037 kg

Certifications UL

UL File No.: E29184

CSA File No.: 012528

IEC/EN 60947

CSA

CSA-C22.2 No. 14-05

CE

CSA Class No.: 3211-03

CSA-C22.2 No. 94-91

IEC/EN 60947-5

UL 508

UL Category Control No.: NKCR

VDE 0660

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Design With thumb-grip

Classical Electric connection type Screw connection Fitted with: Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y General

Degree of protection IP66

NEMA 12 Lifespan, mechanical 100,000 Operations Opening diameter 22.5 mm Operating frequency 2000 Operations/h

Operating torque 0.3 Nm Product Category RMQ-Titan Size Front diameter: 29.7 mm Switching angle 60 ° Type Selector switch actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-DT No Connection type Screw connection Actuator

Actuator color Black Actuator fun...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-WRK3/K20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.