

INDUSTRIAL COMPONENT DATA

M22-WKV 216874 Y7-216874 EATON ELECTRIC Selector switch, toggle, V position, black, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: M22-WKV



Manufacturer	EATON - MOELLER
MPN / Reference	M22-WKV
Catalog number	Y7-216874
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-1C8BB0C707
Generated	2026-08-04

Product Overview

Selector switch, toggle, V position, black, maintained

M22-WKV

Eaton Moeller® series M22 Changeover switch, RMQ-Titan, With thumb-grip, maintained, 2 positions (V position), Bezel: titanium

Changeover switch, Product range: RMQ-Titan, Single unit, Design: With thumb-grip, maintained, 2 positions (V position), Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Selector switch Catalog Number 216874 Model Code M22-WKV EAN 4015082168742 Product Length/Depth 46 mm Product Height 30 mm Product Width 30 mm Product Weight 0.013 kg
Compliances CE Marked Certifications EN 60947-5

UL 508

IEC 60947-5

CSA Std. C22.2 No. 14-05

CSA Std. C22.2 No. 94-91

VDE

CSA Class No.: 3211-03

IEC/EN 60947-5

VDE 0660

CSA

CSA File No.: 012528

CSA-C22.2 No. 94-91

CE

IEC/EN 60947

UL

UL Category Control No.: NKCR

UL File No.: E29184

CSA-C22.2 No. 14-05

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Color Black Design With thumb-grip

Classical Fitted with: Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y

General

Accessories Thumb grip Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical

100,000 Operations Opening diameter 22.5 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm

Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front diameter: 29.7 mm Switching angle 60 °

Type Selector switch actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11

ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min

40 °C Ambie...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-WKV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.