

INDUSTRIAL COMPONENT DATA

Q18LWK3R1-RT/WB 072341 Q18LWK3R1-RT-WB EATON ELECTRIC Illuminated selector switch actuator, 3 positions, red..

Brand: EATON - MOELLER | Manufacturer Part Number: Q18LWK3R1-RT/WB



Manufacturer	EATON - MOELLER
MPN / Reference	Q18LWK3R1-RT/WB
Catalog number	Q18LWK3R1-RT-WB
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-F561BDF0E8
Generated	2026-08-02

Product Overview

Illuminated selector switch actuator, 3 positions, red, maintained, +filament lamp 24V

Light selector. 16 mm. 18x18 mm. 3 positions. Interlocking. Red. With filament lamp. 24 V AC/DC

Illuminated selector switch actuator, maintained/momentary, 45° 45°, 18 × 18 mm, 3 positions, With thumb-grip, red, with VS anti-rotation tab, with filament bulb, 24 V

Illuminated selector switch actuator, Product range: RMQ16, Single unit, Design: With thumb-grip, maintained/momentary, with VS anti-rotation tab, with filament bulb, 24 V, 3 positions, Color Thumb-grip: red, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: 18 × 18 mm, Degree of Protection: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Illuminated selector switch actuator, maintained/momentary, 45° 45°, 18 × 18 mm, 3 positions, With thumb-grip, red, with VS anti-rotation tab, with filament bulb, 24 V Illuminated selector switch actuator, Product range: RMQ16, Single unit, Design: With thumb-grip, maintained/momentary, with VS anti-rotation tab, with filament bulb, 24 V, 3 positions, Colour Thumb-grip: red, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: 18 × 18 mm, Degree of Protection: IP65 Delivery program

Product range RMQ16 Basic function Illuminated selector switch actuator Single unit/Complete unit Single unit Design With thumb-grip maintained/momentary Function: [= spring-return] 45°45° Description with VS anti-rotation tab

with filament bulb, 24 V 3 positions Colour Thumb-grip red Degree of Protection IP65 Connection to SmartWire-DT no Front dimensions 18 × 18 mm Technical data

General Standards IEC/EN 60947 Lifespan, mechanical [Operations] > 3 x 10⁶ Operating frequency [Operations/h] ? 1800 Operating torque ? 0.2 Nm Degree of protection, IEC/EN 60529 IP65 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperatureOpen -25 - +60 °C Ambient temperatureEnclosed - 25 - 40 °C

Mounting position As required Mechanical shock resistance > 40

according to IEC 60068-2-27

Shock duration 11 ms

Sinusoidal g Terminal capacities 0.5 - 1.0 mm² Blade terminal 2.8 x 0.8 mm to DIN 46244 Fast-on connectors 2.8 x 0.8 mm to DIN 46247 an...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q18LWK3R1-RT/WB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.