

INDUSTRIAL COMPONENT DATA

XN-1SSI 140153 Y7-140153 EATON ELECTRIC Serial interface module XI/ON, SSI

Brand: EATON - MOELLER | Manufacturer Part Number: XN-1SSI



Manufacturer	EATON - MOELLER
MPN / Reference	XN-1SSI
Catalog number	Y7-140153
Category	Fieldbus, decentr. periphery - communication module
Minimum order	1 Pcs
Document ID	EO-6A5609DD93
Generated	2026-08-03

Product Overview

Serial interface module XI/ON, SSI

XN-1SSI

Eaton XN Serial interface module XI/ON, SSI

The XI/ON standard I/O system offers the right I/O solution for every application due to its great modularity and large variety of functions. Pluggable modules, hot-swapping of modules, wiring on the basic module screw or tension spring, modules' mechanical coding. The standard gateways support the CANopen bus systems, PROFIBUS-DP deviceNet and Ethernet.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XION
--------------	---

Additional Product Information

General specifications

Product Name Eaton XN Communication module Catalog Number 140153 Model Code XN-1SSI EAN 7640130120099

Product Length/Depth 55.4 mm Product Height 74.1 mm Product Width 12.6 mm Product Weight 0.033 kg Certifications

Certified by UL for use in Canada

UL 508

UL Recognized

CSA-C22.2 No. 142

UL report applies to both US and Canada

UL Category Control No.: NRAQ, NRAQ7

cULus

IEC/EN 61000-6-4

UL File No.: E205091

CSA Class No.: 2252-01, 2252-81

CE

IEC/EN 6113-2

IEC/EN 61131-2

IEC/EN 61000-6-2 Features & Functions

Features Fieldbus connection over separate bus coupler possible Fitted with: Potential separation General
Cable length 30 m, RS232 Interface Channels CL, D Current consumption 25 mA, from supply terminal
50 mA, from module bus, Analog input modules Degree of protection IP20 Insulation resistance 500 V, Control/main circuit
500 V, Control/main circuit enclosure Mounting method Rail mounting possible Resistance 120 Ω (conductor impedance)
Suitable for Base modules without C-Connection, for sensor feeding: 4-wire Type Used with XN-S4T-SBBS
XN-S4S-SBBS Voltage type DC Ambient conditions, mechanical
Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Mechanical,
According to IEC/EN 60068-2-27
Continuous according to IEC/EN 60068-2-29 Vibration resistance According to IEC/EN 60068-2-6 Climatic environmental
conditions
Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Ambient st...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-1SSI with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.