

INDUSTRIAL COMPONENT DATA

TSSD1CO 167391 Y7-167391 EATON ELECTRIC Series connection time switch 24 hrs., segments, 3 TLE

Brand: EATON - MOELLER | Manufacturer Part Number: TSSD1CO



Manufacturer	EATON - MOELLER
MPN / Reference	TSSD1CO
Catalog number	Y7-167391
Category	Analogous time switch for distribution board
Minimum order	1 Pcs
Document ID	EO-11BA68643D
Generated	2026-08-04

Product Overview

Series connection time switch 24 hrs., segments, 3 TLE

TSSD1CO

Eaton Distribution parts. Series connection time switch 24 hrs., segments, 3 TLE

Serially mounted time switch without power reserve, width 52.5mm, 24 hrs. program shortest changeover time 15 min., clock hands for switching the time display and 12h / 24h, clockwise and counterclockwise clock-time correction possible, switching preselection, switching by hand with 3 positions: duration ON / AUTO / OFF permanently, switch-status display, duoFix spring plug-in terminal for 2 conductor each, 1 changeover contacts 16 A/250 V~, 230V / 50 Hz sealable transparent cover.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 167391 Model Code TSSD1CO EAN 4015081638895 Product Length/Depth 65.6 mm Product Height 90 mm Product Width 54 mm Product Weight 0.11 kg Compliances RoHS conform Product specifications

Mounting method DIN rail Equipment heat dissipation, current-dependent 0 W Number of channels 1 Accuracy per day 0 s Ambient operating temperature - max 50 °C Ambient operating temperature - min -25 °C Autonomy in hours 0 hour Autonomy in years 0 year Frequency supply voltage - max 50 Hz Frequency supply voltage - min 50 Hz Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Nominal switching current at 250 V AC 16 A Contact type

Change-over contact Degree of protection IP20 Functions Potential free switch contact

24 h program

Switching preselection

Mains synchronous

Manual operation Voltage type AC Shortest switching time at channel 1 15 min Shortest switching time at channel 2 0 min

Program shift divide 1 15 min Program shift divide 2 0 min Rated operational current for specified heat dissipation (In) 0 A

Switching power LED - max 600 W Static heat dissipation, non-current-dependent 0.9 W Supply voltage - max 230 V

Supply voltage - min 230 V Width in number of modular spacings 3

ETIM for 167391 Modular devices for distribution board/surface mounting (EC002304)

Feature Name

Feature Value

Mounting method (EF000003)

DIN rail

Number of channels (EF000259)

1

Supply voltage (EF004127)

230 V

Volta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TSSD1CO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.