

INDUSTRIAL COMPONENT DATA

TSSD1NO 167389 Y7-167389 EATON ELECTRIC Series connection time switch 24 hrs., series connection time switch..

Brand: EATON - MOELLER | Manufacturer Part Number: TSSD1NO



Manufacturer	EATON - MOELLER
MPN / Reference	TSSD1NO
Catalog number	Y7-167389
Category	Analogous time switch for distribution board
Minimum order	1 Pcs
Document ID	EO-F051938FFF
Generated	2026-08-05

Product Overview

Series connection time switch 24 hrs., series connection time switch, 1 TLE

TSSD1NO

Eaton Distribution parts. Series connection time switch 24 hrs., series connection time switch, 1 TLE

Serially mounted time switch without power reserve, width 17.5mm, 24 hrs. segment program shortest changeover time 15 min., continuous switch ON/OFF, 1 N/O 16A/250V~ sealable transparent cover.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Others and Accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 167389 Model Code TSSD1NO EAN 4015081638888 Product Length/Depth 65.5 mm Product Height 90 mm Product Width 17.5 mm Product Weight 0.071 kg Compliances RoHS conform Product specifications

Mounting method DIN rail Equipment heat dissipation, current-dependent 0 W Number of channels 1 Accuracy per day 0 s Ambient operating temperature - max 50 °C Ambient operating temperature - min -25 °C Autonomy in hours 0 hour Autonomy in years 0 year Frequency supply voltage - max 50 Hz Frequency supply voltage - min 50 Hz Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Nominal switching current at 250 V AC 16 A Contact type Normally open contact Degree of protection IP20 Functions Quartz controlled

Potential free switch contact

Mains synchronous

Manual operation

Switching preselection

24 h program Voltage type AC Shortest switching time at channel 1 15 min Shortest switching time at channel 2 0 min

Program shift divide 1 15 min Program shift divide 2 0 min Rated operational current for specified heat dissipation (In) 0 A

Switching power LED - max 600 W Static heat dissipation, non-current-dependent 0.9 W Supply voltage - max 230 V

Supply voltage - min 230 V Width in number of modular spacings 1

ETIM for 167389 Modular devices for distribution board/surface mounting (EC002304)

Feature Name

Feature Value

Mounting method (EF000003)

DIN rail

Number of channels (EF000259)

1

Supply voltage...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TSSD1NO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.