

INDUSTRIAL COMPONENT DATA

M22-XLED-T 231079 Y7-231079 EATON ELECTRIC Series element, 12-240VAC/DC, for LED 12-30V

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XLED-T



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XLED-T
Catalog number	Y7-231079
Category	Accessories/spare parts for command devices
Minimum order	10 Pcs
Document ID	EO-99C1296AA6
Generated	2026-08-05

Product Overview

Series element, 12-240VAC/DC, for LED 12-30V

M22-XLED-T

Eaton Moeller® series M22 Series element, 12-240VAC/DC, for LED 12-30V

The front elements get their shine with the RMQ-Titan LED light elements! This test element enables all LED elements to illuminated all at once for test purposes. Prerequisite: all LEDs have a module like this and a test button is being planned with it.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory LED Catalog Number 231079 Model Code M22-XLED-T EAN 4015082310790 Product Length/Depth 37 mm Product Height 30 mm Product Width 10 mm Product Weight 0.011 kg

Compliances CE Marked Certifications CSA Std. C22.2 No. 94-91

CSA Std. C22.2 No. 14-05

IEC 60947-5

EN 60947-5

UL 508

CSA

UL Category Control No.: NKCR

IEC/EN 60947-5

CE

CSA-C22.2 No. 14-05

CSA File No.: 012528

CSA Class No.: 3211-03

CSA-C22.2 No. 94-91

UL

UL File No.: E29184 Catalog Notes LED test elements Features & Functions

Functions For de-coupled function test (lamp test) General

Accessory/spare part type Accessory Degree of protection IP20 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Electrical rating

Rated operational voltage 12 - 240 V AC/DC Communication

Connection to SmartWire-DT No Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0.1 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 V...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XLED-T with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.