


INDUSTRIAL COMPONENT DATA

SH0635/3 058247 Y7-58247 EATON ELECTRIC Busbar support, for CI enclosure 250mm, hxD 20x5(10, 15)mm

Brand: EATON - MOELLER | Manufacturer Part Number: SH0635/3



Manufacturer	EATON - MOELLER
MPN / Reference	SH0635/3
Catalog number	Y7-58247
Category	Busbar support
Minimum order	1 Pcs
Document ID	EO-5950D6A40F
Generated	2026-08-05

Product Overview

Busbar support, for CI enclosure 250mm, hxD=20x5(10, 15)mm

Bar holder, for 250mm CI boxes, hxd=20x5(10, 15)mm

Eaton xEnergy Safety Ci LV systems LV switchgear. Busbar support, for CI enclosure 250mm, hxD=20x5(10, 15)mm

Busbar support, for use within housing side walls or within housings, component mounting possible on busbar, busbar supports clearances max. 375mm, interval between busbar centers 50mm, rated operational current Ie=250, 630A, can be used for L1, L2, L3, PE, N: 20x5, L1, L2, L3: 20x10, PE, N, PEN: 20x5, L1, L2, L3, PE, N: 20x15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Insulating Enclosures**

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci busbar enclosure accessory Catalog Number 058247 Model Code SH0635/3 EAN 4015080582472 Product Length/Depth 15 mm Product Height 100 mm Product Width 250 mm Product Weight 0.14 kg

Compliances RoHS conform Product specifications

Special features Type Accessory for busbar enclosures

Prepared enclosures

xEnergy Safety Ci

Accessory/spare part type Busbar support Used with CI43...

L1, L2, L3, PE, N: 20 x 15

CI45...

L1, L2, L3, PE, N: 20 x 5

CI23...

L1, L2, L3: 20 x 10; PE, N, PEN: 20 x 5

Prepared enclosures

Accessory for busbar enclosures

xEnergy Safety Ci Current rating - max 630 A Busbar distance 50 mm Number of poles Five-pole Distance between busbar centers 50 mm Functions For use between two enclosures

Prepared enclosure Rated operation current (Ie) 630 A

250 A

400 A Suitable for Use between two enclosures

ETIM for 058247 Power distribution systems (EC001166)

Feature Name

Feature Value

Number of poles (EF001391)

5

Max. rated current (EF007926)

630 A

Busbar distance (EF002638)

50 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SH0635/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.